



TUNG-SOL

PENTODE

MINIATURE TYPE

OUTLINE
JEDEC 6-2BASE 9 PIN BUTT
JEDEC E9-1

SHARP-CUTOFF PENTODE

FOR
IF AMPLIFIER STAGES
IN TV RECEIVERSCOATED UNIPOTENTIAL CATHODE
ANY MOUNTING POSITIONBASING DIAGRAM
JEDEC 9PM

BOTTOM VIEW

THE 6JD6 IS A SEMI-REMOTE-CUTOFF PENTODE IN THE 9 PIN MINIATURE CONSTRUCTION. IT IS DESIGNED FOR SERVICE IN TELEVISION RECEIVER I.F. AMPLIFIER STAGES. THE SEMI-REMOTE CUTOFF CHARACTERISTICS IS DESIRABLE FOR USE IN AGC CONTROLLED STAGES, EXCEPT FOR HEATER CHARACTERISTICS AND RATINGS, THE 6JD6 IS IDENTICAL TO THE 3JD6 AND THE 4JD6.

DIRECT INTERELECTROCE CAPACITANCES

WITHOUT EXTERNAL SHIELD

GRID 1 TO PLATE - MAX.	0.019	pf
INPUT (G TO H + K + G3 + I.S. + G2)	8.2	pf
OUTPUT (P TO H + K + G3 + I.S. + G2)	3.0	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	300	mA
LIMITS OF APPLIED VOLTAGE		6.3 ± 0.6	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK		200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE			
DC		100	VOLTS
TOTAL DC AND PEAK		200	VOLTS

CONTINUED ON FOLLOWING PAGE

CONTINUED ON FOLLOWING PAGE

MAXIMUM RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

PLATE VOLTAGE	330	VOLTS
GRID 2 SUPPLY VOLTAGE	330	VOLTS
GRID 2 VOLTAGE	SEE RATING CHART	
POSITIVE DC GRID 1 VOLTAGE		0 VOLTS
PLATE DISSIPATION	2.5	WATTS
GRID 2 DISSIPATION - UP TO 165 VOLTS	0.6	WATTS
GRID 1 CIRCUIT RESISTANCE:		
CATHODE BIAS RESISTOR	1	MEGOHM
FIXED BIAS	0.25	MEGOHM

CHARACTERISTICS AND TYPICAL OPERATION

PLATE VOLTAGE	125	VOLTS
GRID 3 VOLTAGE	CONNECTED TO CATHODE AT SOCKET	
GRID 2 VOLTAGE		125 VOLTS
CATHODE BIAS RESISTOR	56	OHMS
PLATE CURRENT	15	mA
GRID 2 CURRENT	4	mA
TRANSCONDUCTANCE	14,000	μMHOS
PLATE RESISTANCE	0.16	MEGOHM
GRID 1 VOLTAGE FOR $G_m = 600 \mu\text{MHOS}$	-4.5	VOLTS

