



6L6-GB

6L6-GB

BEAM POWER TUBE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage 6.3 ac or dc volts

Current 0.9 amp

Direct Interelectrode Capacitances (Approx.):^oGrid No.1 to plate. 0.9 μ fGrid No.1 to cathode & grid No.3,
grid No.2, and heater 11.5 μ fPlate to cathode & grid No.3,
grid No.2, and heater 9.5 μ f

Mechanical:

Mounting Position Any

Maximum Overall Length 4-1/4"

Maximum Seated Length 3-11/16"

Maximum Diameter 1-9/16"

Bulb T12

Base Medium-Shell Octal 7-Pin (JETEC No.B7-12),

Short Medium-Shell Octal 7-Pin

with External Barriers, Style A (JETEC No.B7-111),

or Short Medium-Shell Octal 7-Pin

with External Barriers, Style B (JETEC No.B7-119)


Basing Designation for BOTTOM VIEW 7AC

Pin 1—No Con-
nection

Pin 2—Heater

Pin 3—Plate

Pin 4—Grid No.2



Pin 5—Grid No.1

Pin 7—Heater

Pin 8—Cathode,
Grid No.3AF POWER AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE 360 max. volts

GRID-No.2 (SCREEN-GRID) VOLTAGE 270 max. volts

GRID-No.2 INPUT 2.5 max. watts

PLATE DISSIPATION 19 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode 180 max. volts

Heater positive with respect to cathode 180 max. volts

Typical Operation and Characteristics:

Fixed-Bias Operation

Plate Voltage 200 250 300 350 volts

Grid-No.2 Voltage 200 250 200 250 volts

Grid No.1 (Control-Grid)

Voltage -11.5 -14 -12.5 -18 volts

^o Without external shield.



6L6-GB

BEAM POWER TUBE

Peak AF Grid-No.1 Voltage. . .	11.5	14	12.5	18	volts
Zero-Signal Plate Current. . .	52	72	48	54	ma
Max.-Signal Plate Current. . .	57	79	55	66	ma
Zero-Signal Grid-No.2 Current.	3.5	5	2.5	2.5	ma
Max.-Signal Grid-No.2 Current.	5.7	7.3	4.7	7	ma
Plate Resistance (Approx.) . .	35000	22500	35000	33000	ohms
Transconductance	5300	6000	5300	5200	μ hos
Load Resistance.	3000	2500	4500	4200	ohms
Total Harmonic Distortion. . .	9	10	11	15	%
Max.-Signal Power Output . . .	4	6.5	6.5	10.8	watts

Cathode-Bias Operation

Plate-Supply Voltage	200	250	300	volts
Grid-No.2 Supply Voltage	200	250	200	volts
Cathode Resistor	186	167	218	ohms
Peak AF Grid-No.1 Voltage. . . .	11.5	14	12.7	volts
Zero-Signal Plate Current. . . .	55	75	51	ma
Max.-Signal Plate Current. . . .	56	78	54.5	ma
Zero-Signal Grid-No.2 Current. .	4.2	5.4	3	ma
Max.-Signal Grid-No.2 Current. .	5.6	7.2	4.6	ma
Load Resistance.	3000	2500	4500	ohms
Total Harmonic Distortion. . . .	9	10	11	%
Max.-Signal Power Output	4	6.5	6.5	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max. megohm
For cathode-bias operation	0.5 max. megohm

AF POWER AMPLIFIER - Class A₁*Triode Connection - Grid No.2 Connected to Plate***Maximum Ratings, Design-Center Values:**

PLATE VOLTAGE.	275 max.	volts
PLATE DISSIPATION.	19 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	180 max.	volts
Heater positive with respect to cathode.	180 max.	volts

Typical Operation and Characteristics:

	<i>Fixed Bias</i>	<i>Cathode Bias</i>	
Plate-Supply Voltage	250	250	volts
Grid-No.1 (Control-Grid) Voltage	-20	-	volts
Cathode Resistor	-	490	ohms
Peak AF Grid-No.1 Voltage. . . .	20	20	volts
Zero-Signal Plate Current. . . .	40	40	ma
Max.-Signal Plate Current. . . .	44	42	ma
Plate Resistance (Approx.)	1700	-	ohms



6L6-GB

6L6-GB

BEAM POWER TUBE

	Fixed Bias	Cathode Bias	
Amplification Factor	8	—	
Transconductance	4700	—	μ hos
Load Resistance	5000	6000	ohms
Total Harmonic Distortion	5	6	%
Max.—Signal Power Output	1.4	1.3	watts

Maximum Circuit Values:

Grid-No.1—Circuit Resistance:

For fixed-bias operation	0.1 max. megohm
For cathode-bias operation	0.5 max. megohm

PUSH-PULL AF POWER AMPLIFIER - Class A₁**Maximum Ratings, Design—Center Values:**

PLATE VOLTAGE	360 max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	270 max.	volts
GRID-No.2 INPUT	2.5 max.	watts
PLATE DISSIPATION	19 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	180 max.	volts
Heater positive with respect to cathode.	180 max.	volts

Typical Operation and Characteristics:*Unless otherwise specified, values are for 2 tubes*

	Fixed Bias		Cathode Bias		
Plate Voltage	250	270	250	270	volts
Grid-No.2 Voltage	250	270	250	270	volts
Grid-No.1 Voltage	-16	-17.5	—	—	volts
Cathode Resistor	—	—	124	124	ohms
Peak AF Grid-No.1-to—					
Grid-No.1 Voltage	32	35	35.6	28.2	volts
Zero-Signal Plate Current	120	134	120	134	ma
Max.—Signal Plate Current	140	155	130	145	ma
Zero-Signal Grid-No.2					
Current	10	11	10	11	ma
Max.—Signal Grid-No.2					
Current	16	17	15	17	ma
Plate Resistance (Approx., per tube)	24500	23500	—	—	ohms
Transconductance					
(Per tube)	5500	5700	—	—	μ hos
Effective Load Resistance (Plate to plate)	5000	5000	5000	5000	ohms
Total Harmonic Distortion	2	2	2	2	%
Max.—Signal Power Output	14.5	17.5	13.8	18.5	watts

Maximum Circuit Values:

Grid-No.1—Circuit Resistance:

For fixed-bias operation	0.1 max. megohm
For cathode-bias operation	0.5 max. megohm



6L6-GB

BEAM POWER TUBE

PUSH-PULL AF POWER AMPLIFIER - Class AB₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE	360 max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	270 max.	volts
GRID-No.2 INPUT	2.5 max.	watts
PLATE DISSIPATION	19 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 max.	volts

Typical Operation:

Values are for 2 tubes

	Fixed Bias		Cathode Bias	
Plate Voltage	360	360	360	volts
Grid-No.2 Voltage	270	270	270	volts
Grid-No.1 (Control-Grid)				
Voltage*	-22.5	-22.5	-	volts
Cathode Resistor.	-	-	248	ohms
Peak AF Grid-No.1-to-				
Grid-No.1 Voltage	45	45	40.6	volts
Zero-Signal Plate Current.	88	88	88	ma
Max.-Signal Plate Current.	132	140	100	ma
Zero Signal Grid-No.2				
Current	5	5	5	ma
Max.-Signal Grid-No.2				
Current	15	11	17	ma
Effective Load Resistance				
(Plate to plate).	6600	3800	9000	ohms
Total Harmonic Distortion	2	2	4	%
Max.-Signal Power Output	26.5	18	24.5	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:*

For fixed-bias operation.	0.1 max.	megohm
For cathode-bias operation.	0.5 max.	megohm

PUSH-PULL AF POWER AMPLIFIER - Class AB₂

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE	360 max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	270 max.	volts
GRID-No.2 INPUT	2.5 max.	watts
PLATE DISSIPATION	19 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	180 max.	volts
Heater positive with respect to cathode	180 max.	volts

* The type of input coupling used should not introduce too much resistance in the grid-No.1 circuit. Transformer- or impedance-coupling devices are recommended.



6L6-GB

BEAM POWER TUBE

6L6-GB

Typical Operation:

Values are for 2 tubes

Plate Voltage.	360	360	volts
Grid-No.2 Voltage.	225	270	volts
Grid-No.1 (Control-Grid) Voltage.	-18	-22.5	volts
Peak AF Grid-No.1-to-			
Grid-No.1 Voltage.	52	72	volts
Zero-Signal Plate Current.	78	88	ma
Max.-Signal Plate Current.	142	205	ma
Zero-Signal Grid-No.2 Current.	3.5	5	ma
Max.-Signal Grid-No.2 Current.	11	16	ma
Effective Load Resistance			
(Plate to plate)	6000	3800	ohms
Total Harmonic Distortion.	2	2	%
Max.-Signal Power Output	31	47	watts


Maximum Circuit Values:

Grid-No.1-Circuit Resistance:▲

For fixed-bias operation 0.1 max. megohm

For cathode-bias operation Not recommended

▲ Driver stage should be capable of supplying the specified driving power at low distortion to the No.1 grids of the A₂ stage. To minimize distortion, the effective resistance per grid-No.1 circuit of the A₂ stage should be held at a low value. For this purpose, the use of transformer coupling is recommended.



6L6-GB



6L6-GB

AVERAGE PLATE CHARACTERISTICS




PLATE MILLIAMPERES
TUBE DIVISION


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-4580R2



6L6-GB

6L6-GB AVERAGE CHARACTERISTICS




6L6-GB



6L6-GB

AVERAGE PLATE CHARACTERISTICS TRIODE CONNECTION



TUBE DIVISION

92CM-4966R2

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



6L6-GB

6L6-GB

OPERATION CHARACTERISTICS

