


TUNG-SOL

THREE TRIODES

COATED UNIPOTENTIAL CATHODE

FOR SYNC CLIPPER AND
GATED AGC AMPLIFIER
SERVICE IN TV RECEIVERS


ANY MOUNTING POSITION



BUTTON
12 PIN BASE E12-70

OUTLINE DRAWING
JEDEC 9-56

GLASS BULB



BASING DIAGRAM
JEDEC 12BY

BOTTOM VIEW

THE 6Q11 CONSISTS OF THREE TRIODES IN A 12 PIN COMPACT CONSTRUCTION. TWO OF THE TRIODES HAVE A HIGH MU, THE OTHER HAS A MEDIUM MU. ONE OF THE HIGH MU SECTIONS IS ESPECIALLY SHIELDED FROM THE OTHER SECTIONS. EACH ELEMENT IS BROUGHT OUT TO A SEPARATE BASE PIN. THE 6Q11 IS DESIGNED FOR SYNC CLIPPER AND GATED AGC AMPLIFIER SERVICE IN TV RECEIVERS. THE HEATER MAY BE OPERATED FROM A TRANSFORMER OR IN A SERIES STRING.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

	TRIODE 1	TRIODE 2	TRIODE 3	
GRID TO PLATE	1.8	2.0	2.0	pf
INPUT: G TO (H+K+I.S.)	1.9	1.8	1.8	pf
OUTPUT: P TO (H+K+I.S.)	1.7	0.6	1.7	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM SYSTEM - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	0.60	AMPS
HEATER WARM-UP TIME ^A		11	SECONDS
HEATER SUPPLY LIMITS:			
VOLTAGE OPERATION (AC OR DC)		6.3±0.6	VOLTS
CURRENT OPERATION (AC OR DC)		0.60±.04	AMPS
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE			
TOTAL DC AND PEAK		200	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE			
DC		100	VOLTS
TOTAL DC AND PEAK		200	VOLTS

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS

DESIGN MAXIMUM SYSTEM - SEE EIA STANDARD RS-239

	TRIODE 1	TRIODE 2 & 3	
PLATE VOLTAGE	330	330	VOLTS
NEGATIVE DC GRID VOLTAGE	100	100	VOLTS
POSITIVE DC GRID VOLTAGE	0	0	VOLTS
POSITIVE TRANSIENT GRID VOLTAGE	60	---	VOLTS
POSITIVE STEADY STATE PULSE VOLTAGE ^B	5	---	VOLTS
PLATE DISSIPATION, EACH	3	1.2	WATTS
GRID RESISTANCE	5.0	5.0	MEGOHM

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

CLASS A₁ AMPLIFIER

	TRIODE 1	TRIODE 2 & 3 EACH	
PLATE VOLTAGE	150	100 250	VOLTS
GRID VOLTAGE	0	-1 -2	VOLTS
PLATE CURRENT	22	.5 1.2	MA.
TRANSCONDUCTANCE	2500	1250 1600	μMHOS
AMPLIFICATION FACTOR	18	100 100	
PLATE RESISTANCE	7000	80000 62500	OHMS
GRID VOLTAGE FOR I _b = 10 μA (APPROX.)	-13	--- -4.5	VOLTS

PULSE AMPLIFIER^B

PLATE VOLTAGE	30	---	VOLTS
GRID VOLTAGE	30	---	VOLTS
PEAK CATHODE CURRENT	200	---	MA.
RATIO PLATE CURRENT TO GRID CURRENT	1.0	---	

^A HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

^B THE DURATION OF THE VOLTAGE PULSE MUST NOT EXCEED 15% OF ONE HORIZONTAL SCANNING CYCLE. IN A 525-LINE, 30-FRAME SYSTEM, 15% OF ONE HORIZONTAL SCANNING CYCLE IS 10 MICROSECONDS.