

TECHNICAL DATA


7815AL
7815RAL

PLANAR TRIODES

The EIMAC 7815AL and 7815RAL are ceramic/metal planar triodes specially processed and tested to assure high reliability in airborne service. Evaluation of these tubes is based upon operating conditions in grid- or plate-pulsed oscillator service (transponder) and in grid- or plate-pulsed amplifier service in distance measuring equipment (DME). The testing emphasizes cathode emission capability at reduced heater voltage and high voltage hold-off, both features which are demanded in airline service.

The 7815AL is derived from the 7815/3CPN10A5 and the 7815RAL from the 7815R/3CPX100A5. These new improved tubes also contain the features of the original types, including rugged ceramic/metal construction, low interelectrode capacitance, high transconductance and high μ . The longer grid-anode ceramic insulator of the earlier type is used, making the 7815AL and 7815RAL tubes especially suited for high altitude airborne operation.

In addition to these features, these tubes also incorporate the arc-resistant cathode which assures stable operation under adverse conditions and which minimizes catastrophic failure due to arc-over during circuit malfunction. Both tubes are useable from dc to 3 GHz.



GENERAL CHARACTERISTICS¹

ELECTRICAL

Cathode: Oxide Coated, Unipotential

Heater: Voltage	5.7 ($\pm 2\%$) V
Current, at 5.7 volts	0.95 A
Transconductance (Average):	
$I_b = 70$ mAdc, $E_b = 600$ Vdc	25 mmhos
Amplification Factor (Average)	100
Direct Interelectrode Capacitance (grounded cathode) ² , without heater voltage:	
Grid-Cathode	6.30 pF
Grid-Plate	1.98 pF
Plate-Cathode(maximum)	0.035 pF

1. Characteristics and operating values are based upon performance tests. These figures may change without notice as the result of additional data or product refinement. EIMAC Division of Varian should be consulted before using this information for final equipment design.

2. Capacitance values are for a cold tube as measured in a special shielded fixture.

**MECHANICAL**

Maximum Overall Dimensions:

Length	2.701 in; 68.60 mm
Diameter (7815AL)	1.195 in; 30.35 mm
Diameter (7815RAL)	1.264 in; 32.11 mm
Net Weight (7815AL)	1.8 oz; 48 gm
Net Weight (7815RAL)	2.2 oz; 63 gm
Operating Position	Any
Maximum Operating Temperature:	
Ceramic/Metal Seals	250°C
Anode Core	250°C
Cooling (7815AL)	Conduction and Convection
Cooling (7815RAL)	Forced Air
Terminals	Special

RF POWER AMPLIFIER OR OSCILLATOR

Grid- or Plate-Pulsed

MAXIMUM RATINGS, ABSOLUTE VALUES

DC PLATE VOLTAGE	3500 VOLTS
PEAK PULSE PLATE VOLTAGE	
PLATE PULSED	4500 VOLTS
DC GRID VOLTAGE	-150 VOLTS
INSTANTANEOUS PEAK GRID-	
CATHODE VOLTAGE	
Grid negative to cathode	-700 VOLTS
Grid positive to cathode	250 VOLTS
PULSE PLATE CURRENT	3.0 AMPERE
PULSE GRID CURRENT	1.8 AMPERE
DC CATHODE CURRENT	125 MILLIAMPERES
AVERAGE PLATE DISSIPATION	
Conduction and Convection	
(7815AL)	10 WATTS
Forced Air Cooling(7815RAL) ..	45 WATTS
GRID DISSIPATION (Average) ..	2 WATTS
DUTY FACTOR 1	.0033
PULSE DURATION 1	6 μ s
FREQUENCY	3 GHz

1. For longer pulse duration or higher duty cycle, consult the nearest Varian Electron Tube and Device Group Sales Office, or the Product Manager, EIMAC Division of Varian, Salt Lake City, Utah, or San Carlos, California.

OPERATING CONDITIONS FOR THE 7815AL and 7815RAL in REPRESENTATIVE APPLICATION.

Grid-Pulsed Oscillator

Frequency	1.090 GHz
Heater Voltage	5.7 V
DC Plate Voltage	2000 Vdc
DC Grid Voltage	-75 Vdc
Peak Plate Current	1.1 a
Peak Grid Current	0.8 a
Pulse Duration	0.5 μ s
Duty	0.001
Useful Power Output (Approx.)	750 w

Plate-Pulsed Amplifier

Frequency	1.1 GHz
Heater Voltage	5.7 V
Peak Plate Pulse Voltage	2000 Vdc
DC Grid Voltage	-45 Vdc
Peak Plate Current	1.8 a
Peak Grid Current	1.0 a
Pulse Duration	3.5 μ s
Duty	0.001
Driving Power	300 w
Useful Power Output (Approx.)	1800 w
Gain	8 db
Plate Efficiency	50%

RANGE VALUES FOR EQUIPMENT DESIGN

	Min.	Max.	
Heater Current at 5.7 volts	0.87	1.02	A
Cut-off Bias 1.	---	-25	V
Grid-Plate Capacitance ²	1.85	2.10	pF
Grid-Cathode Capacitance ²	5.60	7.00	pF
Plate-Cathode Capacitance	---	0.035	pF

1. Measured with 1 mA plate current and a plate voltage of 1000 Vdc.

2. Capacitance values as measured with a cold tube and in a shielded socket. When the cathode is heated to the proper temperature the grid-cathode capacitance will increase by approximately 1 pF due to thermal expansion of the cathode support.

APPLICATION

MECHANICAL

MOUNTING - The important dimensions of the tube are carefully controlled with respect to the reference surface as shown on the outline drawing. The reference surface is intended to serve as a tube stop and the location of the tube in the circuit should therefore be determined by this surface coming in positive contact with a precisely positioned member of the socket or cavity. Adherence to this practice will assure both mechanical and electrical interchangeability of all tubes of a given type. If a non-designated surface is used as a tube stop, faulty positioning of the tube in the cavity and possible incomplete electrical contact can result in improper tuning, reduced power output and damage to the cavity, tube or both. Contact surfaces, with reference to the designated tube stop are shown in the outline drawing. Electrical contact to the cathode, grid, anode and also the heater should be restricted to these designated contact areas.

Dimensions should never be taken from sample tubes. Dimensional changes due to normal variations in undimensioned surfaces may occur within the limits specified on the outline drawing. Use of nondesignated electrical contact surfaces might therefore result in incomplete contact or mechanical interference, causing changes in cavity tuning.

Electrical contact should be made by spring finger collets bearing against the previously described contact areas. If connections are employed which do not provide multiple contacts to the designated contact areas, concentration of RF current will result in loss of output power, especially at higher frequencies. The spring contacts used should exert a firm pressure without gouging the plated contact surface. This latter phenomena can result in loose particles of material which can cause arcing or unstable operation of the cavity.

If the tubes are used in applications which call for severe shock or vibration the tube may be clamped in place by the knob or radiator, exerting pressure only on this part of the tube and against the tube stop. No other portion of the tube should be subject to any clamping force. In particular, electrical contacts which utilize set-screws or rigid clamps should be avoided. Such contact schemes can distort the contact surfaces causing undue stress in the metal-to-ceramic seal

area which may result in a vacuum leak. Soldered electrical connections can be made, however great care should be taken during the solder operation to avoid fracture of the seal area due to thermal shock. All contact surfaces should be kept clean to minimize losses.

COOLING - The EIMAC planar triodes are designed to operate at envelope and anode temperatures of up to the maximum rated value of 250°C. However, performance and long-term reliability of any component are improved when it is kept as cool as technically feasible. Therefore, it is recommended that sufficient cooling be provided to keep the anode and seal areas well below the specified maximum temperature, where long tube life and high reliability are of great importance.

The maximum plate dissipation of the 7815AL is 10 watts average power. This can be accomplished by conduction, natural convection or forced air convection cooling. The maximum plate dissipation of the 7815RAL in pulse service is 45 watts average and forced air cooling must be employed at that level. When forced air cooling is used, it is recommended that additional airflow, apart from that flowing through the radiator be used to cool the tube envelope and other tube terminals. A certain amount of conduction cooling is usually inherent in the contact finger configuration. It should be noted, however, that spring fingers provide poor heat conduction and measurements have shown a temperature difference as much as 50°C between the contact finger and contact area.

It is suggested that in all new applications the envelope temperature be measured, especially if the tube is used close to the upper temperature limit. The temperature can easily be determined by the use of Tempilaq paint (Tempil Division, Big Three Industrial Gas & Equipment Co., Hamilton Blvd., So. Plainfield N.J. 07080) or Temp-Plate stickers (Pydrodyne, Inc., 1001 Colorado, Santa Monica, Calif. 90404)

ELECTRICAL

HEATER VOLTAGE - The rated heater voltage for either tube type is 5.7 volts and should be controlled within $\pm 2\%$ to obtain maximum tube life and to minimize variations in circuit performance.



The rated heater voltage is optimum for most existing airborne applications such as DME and transponder systems. However, there are other applications where a different heater voltage than the nominal should be used to obtain the longest possible tube life. Depending on pulse width, power output and frequency of oscillation used a different heater voltage may be better for long reliable life. Electron transit time is not necessarily small with respect to the period of oscillation and the amount of driving power diverted will contribute to the cathode heating by electron bombardment.

The proper adjustment of the heater voltage must be made to compensate for this additional heating, which depends on operating frequency and duty cycle employed.

INTERELECTRODE CAPACITANCES - As indicated, the capacitance values are shown for measurements made with no heater voltage. The cathode to grid and cathode to plate capacitance will increase with the application of the heater voltage, due to the thermal expansion of the cathode support. Typically, the increase in the grid to cathode capacitance will be 15%, or more, depending on the heater voltage. Since the heater voltage can vary depending on use, data taken without heater voltage is more useful for control of tube-to-tube uniformity. The grid to anode capacitance is not effected by the application of the heater voltage.

CIRCUIT TUNING - Especially under grid pulse conditions, it is important that the tube does not lose bias or momentarily go into a CW

mode. Either of these events may result in tube failure. It is suggested that provision be made for initial circuit tune-up at reduced anode voltage and for extra tube protection when the circuit adjustment is critical. The average grid dissipation capability of these tubes is 2.0 watts. For many applications the limiting factor is often not anode dissipation or cathode emission capability, but grid dissipation. If pulse width control is lost in pulse applications the grid can exceed safe operating temperatures in 50 ms or less. Appropriate circuit protection during tune up is therefore recommended.

CATHODE OPERATION - The 7815AL and 7815RAL contain an arc-resistant cathode. Performance in the field and laboratory indicates these tubes are capable of withstanding some abuse due to high voltage arcs, however, poor circuit adjustment in the field may result in shortened tube life. It is, therefore, suggested that wherever feasible, the plate supply be designed such that its impedance limits the short circuit current to within five to ten times the maximum forward current. For pulse service the peak current should be limited to the values listed. Higher pulse width and duty cycles than given can be obtained with proper derating of the current. For this and special applications it is recommended that the user request additional information pertaining to his special application from the nearest Varian Electron Tube and Devices Field Office, or the Product Manager, Eimac Division of Varian, Salt Lake City, Utah or San Carlos, California.



EIMAC 7815AL/7815RAL


TYPICAL

CONSTANT CURRENT CHARACTERISTICS

FOR PULSE OPERATION

$E_f = 5.7$ VOLTS

— PEAK PLATE CURRENT — AMPERES
 --- PEAK GRID CURRENT — AMPERES



CURVE #MA-2372



EIMAC 7815AL/7815RAL
TYPICAL
CONSTANT GRID VOLTAGE
CHARACTERISTICS

FOR PULSE OPERATION

$E_f = 5.7$ VOLTS

— PEAK PLATE CURRENT (i_b)
- - - PEAK GRID CURRENT (i_c)

e_c = PEAK POSITIVE GRID VOLTAGE IN VOLTS





PLATE VOLTAGE (V)

CURVE #MA-2373

ELECTRODE CONTACT AREA				
DIM	MIN.	MAX.	MIN.	MAX.
AA	.035	.361	.89	9.17
AB	1.185	1.265	30.10	32.14
AC	1.534	1.728	38.96	43.89
AD	1.475	1.815	37.47	46.10
	DIM. IN INCHES		DIM. IN MILLIMETERS	

DIMENSION DATA					
DIM. IN INCHES			DIM. IN MILLIMETERS		
MIN.	MAX.	DIM	MIN.	MAX.	NOTES
1.185	1.875	A	46.10	47.62	
	1.534	B		38.96	
	1.475	C		37.46	
1.289	1.329	D	32.74	33.76	
.970	1.010	F	24.64	25.65	
.462	.477	G	11.73	12.12	
	.040	H		1.02	
	.185	I		4.70	
.766	.826	J	19.46	20.98	
1.180	1.195	M	29.97	30.35	
1.025	1.035	N	26.04	26.29	c
.752	.792	P	19.10	20.12	d
.655	.665	R	16.64	16.89	c
	.545	S		13.84	
.213	.223	T	5.41	5.66	c
.315	.325	U	8.00	8.26	c
	.086	V		2.18	
	.100	W		2.54	
.840	.860	LA	21.34	21.84	
.427	.447	ZA	10.75	11.35	



KNURLED

NOTES:

- METRIC EQUIVALENTS, TO THE NEAREST .01 mm, ARE FOR GENERAL INFORMATION ONLY & ARE BASED UPON 1 inch = 25.4 mm.
- ECCENTRICITY OF CONTACT SURFACES SHALL BE GAGED FROM CENTER LINE OR REFERENCE & SHALL BE AS FOLLOWS:

CONTACT SURFACE	TIR(MAX)	REFERENCE
ANODE	.020	CATHODE
GRID	.020	CATHODE
HEATER	.012	CATHODE


- DIA'S N, R, T, & U SHALL APPLY THROUGHOUT ENTIRE LENGTH AS DEFINED BY DIM'S AA, AB, AC & AD RESPECTIVELY.
- THIS SURFACE SHALL NOT BE USED FOR CLAMPING OR LOCATING.

7815 AL -



ELECTRODE CONTACT DIMENSION				
DIM	MIN.	MAX.	MIN.	MAX.
AA	.035	.361	.89	9.17
AB	1.185	1.265	30.10	32.14
AC	1.534	1.728	38.96	43.89
AD	1.475	1.815	37.47	46.10
	DIM. IN INCHES		DIM. IN MILLIMETERS	

DIMENSION DATA					
DIM. IN INCHES			DIM. IN MILLIMETERS		
MIN.	MAX.	DIM	MIN.	MAX.	NOTES
1.185	1.875	A	46.10	47.62	
	1.534	B		38.96	
	1.475	C		37.46	
1.289	1.329	D	32.74	33.76	
.970	1.010	F	24.64	25.65	
.462	.477	G	11.73	12.12	
	.040	H		1.02	
.125	.185	I	3.18	4.70	
.766	.826	J	19.46	20.98	
.025	.046	K	.64	1.17	
1.234	1.264	L	31.34	32.11	
1.180	1.195	M	29.97	30.35	
1.025	1.035	N	26.04	26.29	e
.752	.792	P	19.10	20.12	
.655	.665	R	16.64	16.89	
	.545	S		13.84	
.213	.223	T	5.41	5.66	e
.315	.325	U	8.00	8.26	e
	.086	V		2.18	
	.100	W		2.54	
.105	.145	Y	2.67	3.68	c
.650	.850	Z	16.51	21.59	



RADIATOR, SEE NOTE c
SEE NOTES f, b

NOTES:

- METRIC EQUIVALENTS, TO THE NEAREST .01 mm, ARE GIVEN FOR GENERAL INFORMATION ONLY & ARE BASED ON 1 inch = 25.4 mm.
- THIS SURFACE SHALL BE USED TO MEASURE ANODE SHANK TEMPERATURE.
- HOLES FOR EXTRACTOR THROUGH TOP FIN ONLY.

- ECCENTRICITY OF CONTACT SURFACES SHALL BE GAGED FROM CENTER LINE OF REFERENCE & SHALL BE AS FOLLOWS:

CONTACT SURFACE TIR(MAX) REFERENCE

ANODE	.020	CATHODE
GRID	.020	CATHODE
HEATER	.012	CATHODE

- DIA'S N, R, T & U SHALL APPLY THROUGHOUT ENTIRE LENGTH AS DEFINED BY DIM'S AA, AB, AC & AD RESPECTIVELY.

- THIS SURFACE SHALL NOT BE USED FOR CLAMPING OR LOCATING.

7815 RAL