



Replacement Type

TYPE 7A2
(ENGLISH BASE)



OUTPUT PENTODE



CHARACTERISTICS

Heater Voltage	...	...	4.0 volts	Grid (g_1) Voltage	...	...	-16.5 volts
Heater Current	...	...	1.2 amp.	Cathode Bias Resistor	...	...	410 ohms
Anode Voltage	...	...	250 volts	Anode Impedance	...	...	80,000 ohms
Anode Current	...	...	34 mA	Mutual Conductance	...	...	2.35 mA/V
Screen (g_2) Voltage	...	...	250 volt	Optimum Load	...	...	7,000 ohms
Screen Current	...	...	6.5 mA	Power Output	...	...	3.5 watts

For characteristic curves refer to type 6F6G.

Replacement Type

TYPE 7A3
(ENGLISH BASE)
HIGH SLOPE
POWER PENTODE



CHARACTERISTICS

Heater Voltage	...	...	4.0 volts	Grid (g_1) Voltage	...	...	-6 volts
Heater Current	...	...	2.0 amp.	Cathode Bias Resistor	...	...	150 ohms
Anode Voltage	...	...	250 volts	Anode Impedance	...	...	60,000 ohms
Anode Current	...	...	32 mA	Mutual Conductance	...	...	10 mA/V
Screen (g_2) Voltage	...	...	250 volts	Optimum Load	...	...	8,500 ohms
Screen Current	...	...	6.0 mA	Power Output	...	...	3.75 watts

For characteristic curves refer to type 6AG6G.