


7D5
7D6
7D8




Replacement Type
TYPE 7D5
(ENGLISH BASE)
POWER PENTODE




Heater Voltage	...	13.0 volts	Control Grid (G1) Voltage	...	-16.5 volts
Heater Current	...	0.315 amp.	Cathode Bias Resistor	...	410 ohms
Anode Voltage	...	250 volts	Anode Impedance	...	80,000 ohms
Anode Current	...	34 mA	Mutual Conductance	...	2.35 mA/V
Screen (G2) Voltage	...	250 volts	Optimum Load	...	7,000 ohms
Screen Current	...	6.5 mA	Power Output	...	3.5 watts

For characteristic curves refer to type 6F6G.




Replacement Type
TYPE 7D6
(ENGLISH BASE)
HIGH SLOPE
POWER PENTODE




Heater Voltage	...	40 volts	Control Grid (G1) Voltage	...	-6 volts
Heater Current	...	0.20 amp.	Cathode Bias Resistor	...	150 ohms
Anode Voltage	...	250 volts	Anode Impedance	...	60,000 ohms
Anode Current	...	32 mA	Mutual Conductance	...	10 mA/V
Screen (G2) Voltage	...	250 volts	Optimum Load	...	8,500 ohms
Screen Current	...	6.0 mA	Power Output	...	3.75 watts

For characteristic curves refer to type 6AG6G.



Replacement Type
TYPE 7D8
(ENGLISH BASE)
HIGH SLOPE
POWER PENTODE



Heater Voltage	...	13.0 volts	Control Grid (G1) Voltage	...	-6 volts
Heater Current	...	0.65 amp.	Cathode Bias Resistor	...	150 ohms
Anode Voltage	...	250 volts	Anode Impedance	...	60,000 ohms
Anode Current	...	32 mA	Mutual Conductance	...	10 mA/V
Screen (G2) Voltage	...	250 volts	Optimum Load	...	8,500 ohms
Screen Current	...	6.0 mA	Power Output	...	3.75 watts

For characteristic curves refer to type 6AG6G