

TUNG-SOL

CATHODE RAY

THE 7DP4 IS A DIRECT VIEW PICTURE TUBE DESIGNED FOR TELEVISION APPLICATIONS. ITS FEATURES INCLUDE:

UNIPOENTIAL CATHODE	ELECTROSTATIC FOCUS
ROUND GLASS CONSTRUCTION	MAGNETIC DEFLECTION
EXTERNAL CONDUCTIVE COATING	EXTERNAL DOUBLE FIELD ION TRAP
4" X 5 1/2" RASTER SIZE	

ELECTRICAL DATA

FOCUSING METHOD		ELECTROSTATIC
DEFLECTING METHOD		MAGNETIC
DEFLECTION ANGLE (APPROX.):	50	DEGREES
DIRECT INTERELECTRODE CAPACITANCES (APPROX.)		
CATHODE TO ALL OTHER ELECTRODES	5	$\mu\mu\text{f}$
GRID #1 TO ALL OTHER ELECTRODES	6	$\mu\mu\text{f}$
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	1500	$\mu\mu\text{f}$
MINIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	400	$\mu\mu\text{f}$

OPTICAL DATA

PHOSPHOR NUMBER	SULFIDE TYPE	P-4
FLUORESCENT COLOR		WHITE
PHOSPHORESCENT COLOR		WHITE
PERSISTENCE		MEDIUM

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM

HEATER VOLTAGE	6.3	VOLTS
HEATER CURRENT	0.6	AMP.
MAXIMUM DC ANODE #2, GRID #3 VOLTAGE ^A	8 000	VOLTS
MAXIMUM DC ANODE #1 VOLTAGE	2 400	VOLTS
MAXIMUM DC GRID #2 VOLTAGE	410	VOLTS
MAXIMUM GRID #1 VOLTAGE:		
DC NEGATIVE-BIAS VALUE	125	VOLTS
DC POSITIVE-BIAS VALUE	0	VOLTS
POSITIVE-PEAK VALUE	2	VOLTS
MAXIMUM DC PEAK HEATER-CATHODE VOLTAGE:		
HEATER NEGATIVE WITH RESPECT TO CATHODE		
DURING WARM-UP PERIOD NOT TO EXCEED 15 SECONDS	410	VOLTS
AFTER EQUIPMENT WARM-UP PERIOD	150	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE	150	VOLTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE	1.5	MEG OHMS

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS

DC ANODE #2, GRID #3 VOLTAGE ^B	6 000	VOLTS
DC GRID #2 VOLTAGE	250	VOLTS
ANODE #1 VOLTAGE FOR FOCUS ^D	1215 TO 1645	VOLTS
DC GRID #1 VOLTAGE ^C	-27 TO -63	VOLTS
MAXIMUM ANODE #1 CURRENT RANGE	-15 TO +10	μAMP

^A THE PRODUCT OF ANODE #2 VOLTAGE AND AVERAGE ANODE #2 CURRENT SHOULD NEVER EXCEED 6 WATTS.

^B BRILLIANCE AND DEFINITION DECREASE WITH DECREASING ANODE #2 VOLTAGE. IN GENERAL, ANODE #2 VOLTAGE SHOULD NOT BE LESS THAN 5,000 VOLTS.

^C VISUAL EXTINCTION OF UNDEFLECTED FOCUSED SPOT.

^D WITH COMBINED GRID #1 BIAS VOLTAGE AND VIDEO SIGNAL VOLTAGE ADJUSTED TO PRODUCE A HIGHLIGHT BRIGHTNESS OF 12 FOOT LAMBERTS ON A 4" BY 5 1/2" PICTURE SIZE.


CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE


MECHANICAL DATA

OVERALL LENGTH	$14 \frac{1}{16} \pm \frac{3}{8}$	INCHES
GREATEST DIAMETER OF BULB	$7 \frac{3}{16} \pm \frac{1}{8}$	INCHES
MIN. USEFUL SCREEN DIAMETER	6	INCHES
BULB CONTACT	RECESSED SMALL CAVITY CAP	J1-21
BASE	SMALL SHELL DUODECAL 7 PIN	12C
BASING		
BULB CONTACT ALIGNMENT		
J1-21 CONTACT ALIGNS WITH PIN POSITION #2 ± 30 DEGREES		



PIN CONNECTIONS

PIN 1 - HEATER
 PIN 2 - GRID #1
 PIN 6 - ANODE #1
 PIN 7 - I_c DO NOT USE
 PIN 10 - GRID #2
 PIN 11 - CATHODE



BOTTOM VIEW

PIN 12 - HEATER
 ANODE CAP:
 GRID NO.3