

GENERAL DATA

Spectral Response	See Curve
Wavelength of Max. Response	6100 $\pm$ 400 Angstroms
Sensitive Material	Cadmium-Sulfide
Shape of Sensitive Area	Circular
Construction	Hermetically Sealed in Glass
8100	Flexible Leads
8100-1	Push-Pin Base
8100-7	Bayonet Base
Outline	See Drawings
Operating Position	Any

ELECTRICAL DATA

RATINGS (Absolute Maximum Values)

Breakdown Voltage ²	400 VAC
Dissipation	
T-amb = 25°C	300 mW
T-amb = 70°C	25 mW
Ambient Temperature Range	-40 to +70 °C
Illumination	Note 3


CHARACTERISTICS

Cell Resistance ⁴	
Illumination 2 FC	
Color Temperature 2870°K	5000 Ohms
Dark Resistance ⁵	500,000 Ohms Min.


NOTES:

1. Minute increases in relative humidity will produce change in color.
2. Measured with cell in complete darkness at a pulse rate of 100 pps, 100 μ sec. duration. Voltage in excess of the rated value may damage the cell. Maximum DC voltage is limited by maximum dissipation and minimum dark resistance rating.
3. Care should be exercised to prevent localized overheating of the sensitive surface when the cell is used with a lens system.
4. Measured after 60 minutes exposure to approximately 50 FC illumination (ambient room light).
5. Measured in complete darkness, 10 seconds after removal of 2 FC illumination.

OUTLINE 8100-1




OUTLINE 8100-7



QUICK REFERENCE DATA

The Sylvania Types, 8100, 8100-1 and 8100-7 are cadmium sulfide photoconductive cells featuring high sensitivity and hermetically sealed in-glass construction. The cell is backfilled with gas for a high dissipation safety factor and high voltage capability and includes a blue-dot compound which turns pink¹ if the cell envelope becomes damaged. They are designed for use in a variety of industrial applications as well as automatic contrast and brightness control in television receivers. They are particularly suited to direct operation of relays.

OUTLINE 8100



SYLVANIA ELECTRIC PRODUCTS INC.

Electronic Components Group
ELECTRONIC TUBE DIVISION
EMPORIUM, PA.

A Technical Publication


MAY, 1965

PAGE 1 OF 4


File Under

PHOTOCONDUCTORS


SPECTRAL RESPONSE




SPECTRAL CHARACTERISTIC OF HUMAN EYE, TUNGSTEN AND FLUORESCENT LAMPS



AVERAGE CHARACTERISTICS



PERMISSIBLE DISSIPATION AS A FUNCTION
OF AMBIENT TEMPERATURE



AVERAGE CHARACTERISTICS

