

JEDEC TYPE 8123
 SPONSOR Western Electric Co.

JEDEC TYPE DESIGNATION
 REGISTRATION FOR PULSED MAGNETRON

GENERAL CHARACTERISTICS

The 8123 is a pulsed magnetron oscillator tube which operates over the tunable frequency range of 16000 to 17000 Mc. The peak power output is approximately 70 kilowatts and the tube is forced-air cooled. The tube uses an integral magnet. Special vibration resistant design features minimized vibration induced frequency modulation.

GENERAL ELECTRICAL DATA

Pre-heat Heater Voltage	12.6 $\pm$ 5% volts
Pre-heat Heater Current at 12.6 Volts	3.25 $\pm$ 0.25 amperes
Minimum Pre-heat Time	270 seconds
Heater Cold Resistance (approx.)	0.4 ohm
Anode-Cathode Capacitance (nominal)	14 μ f

RATINGS, ABSOLUTE SYSTEM

Heater Voltage {max.}	13.9 volts
Heater Current {max.}	3.5 amperes
Heater Surge Current {max.}	13.6 amperes
Peak Anode Current {max.}	14 amperes
Peak Anode Current {min.}	5 amperes
Peak Anode Voltage {max.}	16 kilovolts
Average Power Input {max.}	225 watts
Duty Cycle {max.}	0.001
Pulse Duration {max.}	3.3 microseconds
Pulse Duration {min.}	0.20 microseconds
Rate of Rise of Anode Voltage	
Above 50% Point {max.}	120 KV/ μ sec
Above 50% Point {min.}	40 KV/ μ sec
Output and Input Circuit	
Pressurization {max.}	45 psia
Pressurization {min.}	15 psia
Maximum Altitude without Pressurization:	
Output Circuit	sea level
Input Terminals	10,000 ft.
Body Temperature {max.}	100°C
Cathode Stem Temperature {max.}	275°C
VSWR (Magnetron Load) {max.}	1.5:1
Tuner Torque {max.}	50 in. oz.

TYPICAL OPERATING VALUES

Frequency	16000 to 17000 Mc
Peak Anode Voltage at 17.0 kmc	15.0 kv
Pulling Figure {VSWR 1.5:1}	6 Mc
Pushing Figure {VSWR 1.5:1}	0.06 Mc/AMP
Atmospheric Frequency Shift	
(sea level to 75,000 ft.)	3 Mc

TYPICAL OPERATING VALUES (CONT'D.)

Duty Factor 0.001
 Peak Anode Current 12 amperes
 Stability (% Missing Pulses) <0.001 %
 Peak Power Output 70 kw
 Heater Voltage $8.8 \pm 5\%$ volts

Current Pulse Duration	Voltage Pulse Rate-of- Rise	RF Band Width at 1/4 po pts.	R.M.S. Jitter		
			F _J	V _J	T _J
μsec	KV per μsec (above 50% point)	σ'=1.5:1 worst phase Mc	kc	db	ns
0.25 2.0	60 60	4.0 .50	- 13	- .02	1.5 -

GENERAL MECHANICAL CHARACTERISTICS

Mounting Position Any
 Mounting Support See 4 hole
 Mounting Plate in
 outline drawing
 Weight 7.94 lbs. Max.

Coupling between Tube and Load:


RG 91/U waveguide mates with modified UG 541/U choke flange with clearance holes instead of 6-32 tapped holes.

Cooling Data

To limit rise in body temperature to 50°C for a dissipation of 115 watts - 10 cfm, min.


Pressurization of Output Circuit:

The need for pressurization depends on the particular components used in the output circuit and on the pulse width. In general, pressurization above 15 psia should not be necessary.



NOTES ~

1. THE FREQUENCY INCREASES WHEN DRIVE SHAFT IS DRIVEN IN THE DIRECTION INDICATED BY ARROW.
2. THE TUNING MECHANISM OPERATES SMOOTHLY OVER THE ENTIRE MECHANICAL RANGE WHEN SUBJECTED TO A DYNAMIC TORQUE OF 10 OZ. INCHES MAX. APPLIED AT THE DRIVE SHAFT. IN EQUIPMENT THE MAX. KIN TORQUE SHALL NOT EXCEED 50 OZ. INCHES. THE AXIAL AND RADIAL FORCE APPLIED TO THE DRIVE SHAFT SHALL NOT EXCEED ONE POUND. THE GEAR MUST BE FREE FROM COMPRESSION, FRUIT, AND OTHER IMPERFECTIONS.
3. THE AXIS OF THE CATHODE TERMINAL IS WITHIN A RADIUS OF $3/16$ " OF SPECIFIED LOCATION. (NOTE A MINUTES)
4. THE LIMITS ON LOCATION IN X-Y PLANE GUIDE INPUT AND OUTPUT TERMINAL WIRE ANGULAR AS WELL AS LATERAL DEVIATIONS.
5. NO CLAMPING ON THIS DIAMETER.
6. THE CATHODE TERMINAL IS SYNGENTRIC WITH THE CATHODE TERMINAL WITHIN .010".
7. PREVENT: MAINTAIN MINIMUM CLEARANCE OF 8 INCHES BETWEEN THIS MAGNET AND MAGNETIC MATERIALS. (MAGNETS, STEEL TOOLS, PLATES, ETC.)
8. THE DRIVING OF THE HOLE GUIDE AND THE INPUT SHAFT BE ENCLOSED BY A DUST COVER WHEN TOOL IS NOT IN USE.
9. ALL METAL SURFACES COVERED BY GRAY FINISH EXCEPT THOSE MARKED "S".
10. "S" IS PROVIDED WITH INTERNAL STOP FOR IMPACT CAUSED BY UNEXPECTEDLY THIN DRIVE SHAFT FOR A MAX. OF (50) IMPACTS.
11. THESE DIMENSIONS DEFINE EXTREMITIES OF CYLINDRICAL SECTIONS GIVEN BY .250 AND .750 DIMENSIONS.
12. CASE PLATE CAN BE SEaled WITH GASKET C-660001 SPECIFIED IN SPECIFICATIONS AS SHOWN ON C-660000. WHEN SEaled IN THIS MANNER, THE LEAKAGE RATE SHALL NOT EXCEED 0.1 CUBIC INCH PER MINUTE AT 15 PSI.



8/23 MAGNETRON