

8AW8A

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 8AW8A is the same as the 6AW8A except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.4	volts
Warm-up time (Average).	11	sec

8B10

Twin Diode— Medium-Mu-Twin Triode

DUODECAR TYPE

The 8B10 is the same as the 6B10 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.5	volts
Warm-up time (Average).	11	sec

8BA8A

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 8BA8A is the same as the 6BA8A except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.4	volts
Warm-up time (Average).	11	sec



8BH8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

The 8BH8 is the same as the 6BH8 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.4	volts
Warm-up time (Average).	11	sec

8BN8

Twin Diode—High-Mu Triode

9-PIN MINIATURE TYPE

The 8BN8 is the same as the 6BN8 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	8.4	volts
Warm-up time (Average).	11	sec

8BQ5

Power Pentode

9-PIN MINIATURE TYPE

The 8BQ5 is the same as the 6BQ5 except for the following items:

Heater Characteristics and Ratings:

Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	8.0	volts
Warm-up time (Average).	11	sec





8AU8
TO
8BH8

8AU8

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8AU8 is the same as the 6AU8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	8.4	volts
Current	0.45	amp

8AW8-A

HIGH-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8AW8-A is the same as the 6AW8-A except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	8.4	volts
Current	0.45	amp

8BH8

MEDIUM-MU TRIODE— SHARP-CUTOFF PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8BH8 is the same as the 6BH8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	8.4	volts
Current	0.45	amp

8BN8
TO
8CG7



8BN8

TWIN DIODE—HIGH-MU TRIODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8BN8 is the same as the 6BN8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	8.4	volts
Current	0.45 ± 6%	amp

8BQ5

POWER PENTODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8BQ5 is the same as the 6BQ5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	8	volts
Current	0.6	amp
Warm-up time (Average)	11	sec

8CG7

MEDIUM-MU TWIN TRIODE

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 8CG7 is the same as the 6CG7 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	8.4	volts
Current	0.45	amp