

CHARACTERISTICS

GENERAL DATA

Focusing Method	.	.	.	.	.	Electrostatic
Deflecting Method	.	.	.	.	.	Electrostatic
Types*	Fluorescence	Phosphorescence	Persistence			
8CP1	Green	—	Medium			
8CP2	Blue-Green	Green	Long			
8CP4	White	—	Medium			
8CP5	Blue	—	Veryshort			
8CP7	Blue	Yellow	Long			
8CP11	Blue	—	Short			

*In addition to the types shown, the 8CP- can be supplied with several other screen phosphors.

ELECTRICAL DATA

Heater Voltage	.	.	.	.	.	6.3 Volts
Heater Current	.	.	.	.	.	$0.6 \pm 10\%$ Amperes
Direct Interelectrode Capacitances (Approx.)						
Cathode to All Other Electrodes	.	.	.	.	.	10 $\mu\mu\text{f}$
Grid No. 1 to All Other Electrodes	.	.	.	.	.	8 $\mu\mu\text{f}$
Between Deflecting Plates 1-2 ¹	.	.	.	.	.	4 $\mu\mu\text{f}$
Between Deflecting Plates 3-4 ¹	.	.	.	.	.	2 $\mu\mu\text{f}$
Deflecting Plate 1 to All Other Electrodes Except DP2	.	.	.	.	.	8 $\mu\mu\text{f}$
Deflecting Plate 2 to All Other Electrodes Except DP1	.	.	.	.	.	8 $\mu\mu\text{f}$
Deflecting Plate 3 to All Other Electrodes Except DP4	.	.	.	.	.	6 $\mu\mu\text{f}$
Deflecting Plate 4 to All Other Electrodes Except DP3	.	.	.	.	.	6 $\mu\mu\text{f}$

MECHANICAL DATA

Minimum Useful Screen Diameter	.	.	.	.	.	7 $\frac{1}{2}$ Inches
Bulb Contact (Recessed Small Ball)	.	.	.	.	.	J1-22
Base (Medium Shell Diheptal 12-Pin)	.	.	.	.	.	B12-37
Basing	.	.	.	.	.	14J
Base alignment D1-D2 trace aligns with Pin No. 5						
and No. 12	.	.	.	.	.	± 10 Degrees
Positive voltage on D1 deflects beam toward Pin No. 5						
Positive voltage on D3 deflects beam toward Pin No. 2						


RATINGS

MAXIMUM RATINGS (Absolute Maximum Values)


Anode No. 3 Voltage	.	.	.	.	.	6,600 Volts	dc
Anode No. 2 Voltage	.	.	.	.	.	6,600 Volts	dc
Ratio of Anode No. 3 Voltage to Anode No. 2 Voltage	.	.	.	.	.	2.3:1 Volts	dc
Anode No. 1 Voltage	.	.	.	.	.	2,750 Volts	dc
Grid No. 1 Voltage	.	.	.	.	.		
Negative Bias Value	.	.	.	.	.	220 Volts	dc
Positive Bias Value	.	.	.	.	.	0	
Positive Peak Value	.	.	.	.	.	2 Volts	
Peak Heater Cathode Voltage	.	.	.	.	.		
Heater Negative with Respect to Cathode	.	.	.	.	.	140 Volts	
Heater Positive with Respect to Cathode	.	.	.	.	.	140 Volts	
Peak Voltage Between Anode No. 2	.	.	.	.	.		
And Any Deflecting Plate	.	.	.	.	.	550 Volts	

QUICK REFERENCE DATA

Special Purpose Tube
8" Direct Viewed
Round Glass Type
Electrostatic Deflection
Electrostatic Focus
Post Deflection Accelerator



153006



SYLVANIA
ELECTRONIC TUBES
A Division of
Sylvania Electric Products Inc.
PICTURE TUBE OPERATIONS
SENECA FALLS, NEW YORK

Prepared and Released By The
TECHNICAL PUBLICATIONS SECTION
EMPORIUM, PENNSYLVANIA

NOVEMBER, 1958

TYPICAL OPERATING CONDITIONS

Anode No. 3 Voltage	4,000 Volts dc
Anode No. 2 Voltage	2,000 Volts dc
Anode No. 1 Voltage	540 to 800 Volts dc
Grid No. 1 Voltage Required for Cutoff ²	-24 to -56 Volts dc
Deflection Factor	
Deflecting Plates 1-2	58 to 81 Volts dc/Inch
Deflecting Plates 3-4	49 to 68 Volts dc/Inch

CIRCUIT VALUES

Grid No. 1 Circuit Resistance	1.5 Megohms Max.
Deflection Circuit Resistance	5.0 Megohms Max.

NOTES:

1. Deflecting Plate 1 is Pin No. 11
Deflecting Plate 2 is Pin No. 10
Deflecting Plate 3 is Pin No. 7
Deflecting Plate 4 is Pin No. 8
2. Visual extinction of undeflected spot.

WARNING:

X-ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at higher than the manufacturer's Maximum Rated Anode Voltage or 16,000 volts, whichever is less.

