



9003

9003

SUPER-CONTROL R-F AMPLIFIER PENTODE

MIDGET TYPE

Heater	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.15	amp.
Direct Interelectrode Capacitances:		
Grid to Plate	0.01 max.	μf
Input	3.4	μf
Output	3.0	μf
Maximum Overall Length		1-13/16"
Maximum Seated Height		1-9/16"
Length from Base Seat to Bulb Top (excluding tip)		1-3/16" $\pm$ 3/32"*
Maximum Diameter		3/4"
Bulb		T-5-1/2
Base [▲]	Miniature Button 7-Pin	
Pin 1 - Grid	Pin 5 - Plate	
Pin 2 - Cathode	Pin 6 - Screen	
Pin 3 - Heater	Pin 7 - { Cathode, Grid No. 3, Internal Shield	
Pin 4 - Heater		
RCA Socket		Stock No. 9914
Mounting Position	BOTTOM VIEW	Any



Maximum and Minimum Ratings Are Design-Center Values
AMPLIFIER

Plate Voltage	250 max.	volts
Screen Voltage	100 max.	volts
Grid Voltage	-3 min.	volts
Plate Dissipation	1.7 max.	watts
Screen Dissipation	0.3 max.	watt

Typical Operation and Characteristics - Class A₁ Amplifier:

Plate Voltage	250	volts
Screen Voltage	100	volts
Grid Voltage	-3	volts
Plate Resistance	0.7 approx.	megohm
Transconductance	1800	μmhos
Grid Bias for Transcond. of 15 μmhos	-35	volts
Grid Bias for Transcond. of 2 μmhos	-45	volts
Plate Current	6.7	ma.
Screen Current	2.7	ma.

Typical Operation as Mixer in Superheterodyne Circuit:

Plate Voltage	100	250	volts
Screen Voltage	100	100	volts
Grid Voltage #	-10	-10 approx.	volts
Conversion Transconductance		600 approx.	μmhos

* The grid bias is minimum for an oscillator peak voltage of 9 volts. These values are optimum.

▲ The center hole in sockets designed for this base provides for the possibility that this tube type may be manufactured with the exhaust-tube tip at the base end. For this reason, it is recommended that in equipment employing this tube type, no material be permitted to obstruct the socket hole.

Shielding Considerations & Heater-Cathode Connections
for the 9003 are the same as for Type 9001.

← Indicates a change.

* Temporary minimum length = 1-1/16".

OCT. 1, 1943

RCA VICTOR DIVISION

DATA


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

9003



9003

AVERAGE PLATE CHARACTERISTICS



SEPT. 17, 1943

RCA VICTOR DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92C-6288



9003

9003

AVERAGE CHARACTERISTICS



MAY 29, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.


92C-6289

9003



9003

AVERAGE CHARACTERISTICS



MAY 29, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-6290