

PHILIPS „MINIWATT“

Heizspannung		
Tension de chauffage	v_f	= 3,4-4,0 V
Filament voltage		
Heizstrom		ca.
Courant de chauffage	i_f	= env. 0,06 A
Filament current		appr.
Anodenspannung		
Tension anodique	v_a max.	= 150 V
Anode voltage		
Normaler Anodenstrom		
Courant anodique normal	i_a	= 3,5 mA
Normal anode current		
Neg. Gittervorspannung		ca.
Polarisation négative de grille	v_g	= env. 3 V
Negative grid bias		appr.
Verstärkungsfaktor		
Coefficient d'amplification	$g(k)$	= 10
Amplification factor		
Steilheit (max.)	$S_{max.}$	= 0,5 mA/V
Inclinaison (max.)		
Slope (max.)		
Steilheit (norm.)	$S_{norm.}$	= 0,5 mA/V
Inclinaison (norm.)		
Slope (norm.)		
Innerer Widerstand (norm.)		
Résistance intérieure (norm.)	R_i	= 20000 Ohm
Internal resistance (norm.)		
Anoden-Gitterkapazität		
Capacité grille-plaque	C_{ag}	= 2,5 $\mu\mu F$
Anode-grid capacity		
Max. Länge	l	= 83 mm
Longueur max.		
Overall length		
Grösster Durchmesser	d	= 42 mm
Diamètre max.		
Max. diameter		
Sockel		= A 32
Culot		
Base		
Sockelschaltung		= S. I
Connexion du culot		
Base connection		
Anwendung: H.F.-Verstärkung		
Applications: Amplification h.f.		
Function: H.F. amplification		
Z.F.-Verstärkung		
Amplification m.f.		
L.F. amplification		
Audion		
Détecteur		
Detector		
N.F.-Verstärkung		
Amplification b.f.		
L.F. amplification		

**PHILIPS
MINIWATT
A 410**

$V_f = 3,4-4,0V$

$V_{a\max} = 150V$

$I_a = 3,5mA$

$S_{\max} = 0,5mA/V$

$S_{\text{norm}} = 0,5mA/V$

$g(k) = 10$

