


TELEVISION PICTURE TUBE



B8H Base, CT8 Cap

GENERAL

Rectangular Face.....	19 in.	Diagonal
Electrostatic Focus	Magnetic	Deflection
Deflection Angle	110°	Diagonal
Aluminised Screen	White	Fluorescence
Grey Glass.....	75%	Transmission (approx.)
Straight Gun	Non Ion	Trap
External Conductive Coating		

Heater Voltage	V_h	6.3	V
Heater Current	I_h	0.3	A

The cathode ray tube heater should always be connected at the chassis end if used in a series heater chain.

DESIGN CENTRE RATINGS

Maximum Second and Fourth Anode Voltage	$V_{a2, a4(max)}$	20*	kV
Minimum Second and Fourth Anode Voltage	$V_{a2, a4(min)}$	13	kV
Maximum Third Anode Voltage	$V_{a3(max)}$	+ 1000 to -500	V
Maximum First Anode Voltage	$V_{a1(max)}$	700	V
Maximum Heater to Cathode Voltage, Heater Negative (d.c.)	$V_{h-k(max)}$	250	V
Maximum Peak Heater to Cathode Voltage, Heater Negative	$V_{h-k(pk)max}$	400†‡	V
Maximum Impedance Grid to Cathode (50 Hz)	$Z_{g-k(max)}$	0.5	MΩ
Maximum Resistance Grid to Cathode	$R_{g-k(max)}$	1.5	MΩ

All voltages referred to cathode.

* For $I_{a2+a4}=0$.

† Absolute rating.

‡ During a warming-up period not exceeding 45 seconds.

Tubes incorporating a B8H sparkguard base will have a suffix S after the type number. For details of the sparkguard base see separate sheet.

INTER-ELECTRODE CAPACITANCES

Cathode to all	C_{k-all}	§ 3.0	φ 3.5	pF
Grid to all	C_{g-all}	7.0	8.5	pF
Second and Fourth Anode to External Conductive Coating (approx.)	$C_{a2,a4-M}$		1250	pF

§ Inter-electrode capacitances with holder capacitance balanced out.

φ Total inter-electrode capacitances including a typical B8H holder.

TYPICAL OPERATION—Grid Modulation (Voltage referred to cathode)

Second and Fourth Anode Voltage	$V_{a2,a4-k}$	18	18	kV
First Anode Voltage*	V_{a1-k}	400	500	V
Final Anode Current	I_{a2+a4}	350 500	350 500	μA
Third Anode Voltage Range for Focus	V_{a3-k}	0 to 400	0 to 400	V
Average Peak to Peak Picture Modulating Voltage		35.5 40.5	39.5 45	V
Grid to Cathode Voltage for Cut-off of Raster (See chart for limits)	V_{g-k}	-57	-69	V

TYPICAL OPERATION—Cathode Modulation (Voltage referred to grid)

Second and Fourth Anode Voltage	$V_{a2,a4-g}$	18	18	kV
First Anode Voltage*	V_{a1-g}	400	500	V
Final Anode Current	I_{a2+a4}	350 500	350 500	μA
Third Anode Voltage Range for Focus	V_{a3-g}	0 to 400	0 to 400	V
Average Peak to Peak Picture Modulating Voltage		31.5 35.5	34.5 39.5	V
Cathode to Grid Voltage for Cut-off of Raster (See chart for limits)	V_{k-g}	51	62	V

* Within this range a higher First Anode Voltage will provide an improved focus performance.

PICTURE CENTRING

Maximum magnet flux density at centre of neck should not be less than	17 Gs
Maximum distance of centre of magnetic field from reference line	53 mm

NOTE

If this tube is operated at voltages in excess of 16kV, x-ray radiation shielding may be necessary to avoid possible danger of personal injury from prolonged exposure at close range. The normal glass protective viewing window may provide such a safeguard. If the radiation measured in contact with this window does not exceed 0.5 milliröntgens per hour, the window will normally provide adequate protection.

DEFLECTION ANGLES

Height	82°
Width	99°
Diagonal	110°

WEIGHT

Approximate Single Tube Weight : Net	7.2 kg (16 lb)
Packed	9.1 kg (20 lb)



Not to be scaled.

There is an annular region of anti-corona coating with diameters of 30 mm and 100 mm surrounding the CT8 cap, the tube should not be handled in this region.

