


TUNG-SOL

THYRATRON




GLASS BULB

HEATER

6.3 VOLTS 23. AMP.

VERTICAL MOUNTING
POSITION

(BASE DOWN)



BOTTOM VIEW

THE CH1095 IS A ZERO BIAS HYDROGEN THYRATRON DESIGNED TO PASS HIGH CURRENTS IN "CROWBAR" PROTECTIVE CIRCUITS. AS DESCRIBED IN THE APPLICATION NOTES, DESTRUCTIVE ARC CURRENTS ARE SHORT CIRCUITED BY THE CROWBAR TUBE BEFORE DAMAGE OCCURS TO OTHER TUBES OR CIRCUIT ELEMENTS.

THE INSTANTANEOUS RESPONSE, AND ABILITY TO REPEATEDLY CARRY EXTREMELY LARGE CURRENTS, MAKES THE HYDROGEN THYRATRON PARTICULARLY ATTRACTIVE FOR THIS APPLICATION. ONE TYPE CH1095 CAN HANDLE A PEAK CURRENT OF 800 AMPS AT 18 KILOVOLTS. THIS TUBE CONTAINS A HYDROGEN RESERVOIR WHICH PROMOTES LONG LIFE AND PERMITS OPTIMUM GAS PRESSURE ADJUSTMENT FOR VARIOUS CONDITIONS OF OPERATION.

ELECTRICAL DATA

	MIN.	BOGEY	MAX.	
CATHODE HEATER VOLTAGE	6.0	6.3	6.6	VOLTS
CATHODE HEATER CURRENT ($E_f = 6.3$ VOLTS)	15.	16.	22.	AMP.
CATHODE HEATING TIME	10.			MINUTES
RESERVOIR VOLTAGE	3.0	MARKED ON BASE	5.5	VOLTS
RESERVOIR CURRENT			6.5	AMP.
RESERVOIR HEATING TIME	10.			MINUTES

MECHANICAL DATA

TYPE OF COOLING	CONVECTION	
MAX. NET WEIGHT	2 1/4	LBS.
MOUNTING POSITION	ANY	
DIMENSIONS	SEE OUTLINE DRAWINGS	

CONTINUED ON FOLLOWING PAGE

TUNG-SOL


CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS
ABSOLUTE VALUES

D.C. ANODE VOLTAGE	MIN.	MAX.	
FORWARD	2	18	KVOLTS
INVERSE		5	KVOLTS
CATHODE CURRENT			
PEAK		800	AMP.
AVERAGE		1.	AMP.
CONDUCTION TIME PER FAULT		0.1	SECONDS
AVERAGING TIME		80	SECONDS
RECOVERY TIME		50	μ SECONDS
GRID SIGNAL VOLTAGE	1000	2000	VOLTS
GRID IMPEDANCE	50	500	OHMS
GRID VOLTAGE RATE OF RISE	1800		V/ μ SEC.
ANODE DELAY TIME		0.6	μ SECONDS
ANODE VOLTAGE DROP	50	200	VOLTS
AMBIENT TEMPERATURE RANGE	-50	+75	$^{\circ}$ C

APPLICATION NOTES

IN A TYPICAL APPLICATION, A CROWBAR THYRATRON IS CONNECTED IN SERIES WITH A SUITABLE IMPEDANCE ACROSS THE FILTER OF THE HIGH VOLTAGE POWER SUPPLY FOR A HIGH FREQUENCY TRIODE OSCILLATOR. WHENEVER AN ARC OCCURS IN THE OSCILLATOR TUBE, THE RISING CURRENT IS USED TO DELIVER A SUITABLE SIGNAL TO THE GRID OF THE THYRATRON. THE THYRATRON IMMEDIATELY CONDUCTS TO SHORT CIRCUIT THE POWER SUPPLY UNTIL THE PROTECTIVE CIRCUIT BREAKER OPENS 0.1 TO 0.5 SECOND LATER. WITH PROPER CIRCUITRY, THE THYRATRON CAN BE MADE TO RECOVER CONTROL BEFORE THE POWER SUPPLY BREAKER OPENS. IN THIS LATTER CASE, THE OSCILLATOR TUBE IS PROTECTED WITH A MINIMUM INTERRUPTION IN OPERATING TIME.



REFERENCES:

- SMITH, BOB: THE FAULT DIVERTER - A PROTECTIVE DEVICE FOR HIGH-POWER ELECTRON TUBES.
REPORT UCRL-2701 REV. UNIVERSITY OF CALIFORNIA, RADIATION LABORATORIES,
BERKELEY, CALIF.

PARKER, W. V.
AND

HOOVER, M.V.:

GAS TUBES PROTECT HIGH-POWER TRANSMITTERS. ELECTRONICS, JAN. 1956.

POOLITTLE, J. D.:

AD-2045280 HYDROGEN THERMOCAL, 147-001 28705, 11, 24, 1964