

*Excellence in Electronics***TYPE
CK526AX**

The CK526AX is a filament type pentode of subminiature construction designed for use as a power amplifier in portable and wearable equipment. The tinned flexible leads may be soldered or welded directly to the terminals of circuit components without the use of sockets. Standard inline subminiature sockets may be used by cutting the leads to a suitable length.

MECHANICAL DATAENVELOPE: T-2X3 GlassBASE: None (0.016" tinned flexible leads. Length: 1.5" min.
Spacing: 0.048" center-to-center)TERMINAL CONNECTIONS: (Red Dot is adjacent to Lead 1)

Lead 1 Plate	Lead 4 Control Grid
Lead 2 Screen Grid	Lead 5 Filament, Negative ♦
Lead 3 Filament, Positive ♦	



MOUNTING POSITION: Any**ELECTRICAL DATA**RATINGS - ABSOLUTE MAXIMUM VALUES:

Filament Voltage (dc)	1.25 ± 20% volts
Plate Voltage	45 volts
Screen Grid Voltage	45 volts
Cathode Current	1.0 ma.

CHARACTERISTICS AND TYPICAL OPERATION:

Filament Voltage (dc)	1.25 volts
Filament Current	20 ma.
Plate Voltage	22.5 volts
Screen Grid Voltage	22.5 volts
Control Grid Voltage	-1.5 volts
Peak AF Control Grid Voltage	1.5 volts
Plate Current	0.45 ma.
Screen Grid Current	0.12 ma.
Transconductance	400 μ mhos
Plate Resistance	0.22 meg.
Load Resistance	0.05 meg.
Distortion (approx.)	10 percent
Power Output	3.75 mw.

♦ Grid #3 is composed of two deflector plates, one being connected to Lead 3 and the other to Lead 5.





SUBMINIATURE PENTODE

