

Svetlana EF86

High-Performance Audio

Small-Signal Pentode



The Svetlana EF86 is a glass envelope miniature pentode intended for high-quality audio preamplifier service. Close manufacturing specification tolerances and improved processing provide improved reliability and superior sonic performance. The Svetlana EF86 is manufactured in the Svetlana factory in Russia, and is designed to be a direct replacement for any EF86 or 6267 type.

The Svetlana EF86 features:

- Low microphonics and low heater hum induction - suitable for input stages in high-gain microphone preamps, phono preamps or as a gain stage in condenser microphones
- Electrostatic shield is built-in, covers entire inner structure—no external shield required
- Low distortion in pentode or triode connection
- Extended processing and aging for stability and reliability
- Comprehensive static and audio amplifier testing before and after aging

General Characteristics

Electrical

	<i>min.</i>	<i>typ.</i>	<i>max.</i>	
Heater Voltage (AC or DC)	5.7	6.3	6.9	V
Heater Current (typical)		0.2		A
Cathode:		oxide-coated, unipotential		
Cathode-to-heater potential		± 100		V


Mechanical

Operating position:	Any		
Base	9-pin miniature noval		
Basing diagram	JEDEC 9CQ		
Socket	Svetlana SK9A or equivalent		
Cooling	Radiation and convection		
Envelope temperature (max)		200	C
Nominal dimensions:			
Diameter		22 mm (0.867 in)	
Base to top		46.5 mm (1.836 in)	
Overall height		55.5 mm (2.180 in)	
Net weight		13 gm	

Maximum Ratings

DC plate voltage V_p	300	V
Screen grid voltage V_{g2}	200	V
Plate dissipation	1	W
Screen grid dissipation	0.2	W
Cathode current	6.0	mA


Svetlana EF86 Outline drawing



Dimensional Data

Dim.	Millimeters	Inches
A	46.5	1.835
C	55.5	2.180
B	22	0.867

Base pin connections bottom view



Svetlana
ELECTRON DEVICES

Headquarters:
8200 South Memorial Parkway
Huntsville, AL 35802
USA
Phone: 205 882 1344
Fax: 205 880 8077

Marketing & Engineering:
3000 Alpine Road
Portola Valley, CA 94028
USA
Phone: 415 233 0429
Fax: 415 233 0439

www.svetlana.com

Svetlana EF86

High-Performance Audio

Small-Signal Pentode



Svetlana
ELECTRON DEVICES

Typical operation, Class A Connection, Small-signal amplifier

	pentode	triode	
DC plate Voltage	250	250	V
Screen grid voltage	140		V
Cathode bias resistor	1k	3.9k	ohms
Zero-signal plate current	3	0.65	mA
Zero-signal screen grid current	0.6		mA
Plate resistance (approx)	2.5 megohms	65k	ohms
Load resistance	220k	220k	ohms
Total harmonic distortion	5	3.5	%
Maximum voltage output	50	39	vrms

