



ELECTRON TUBE DEPARTMENT ■ **COMPONENTS DIVISION**
INTERNATIONAL TELEPHONE AND TELEGRAPH CORPORATION, CLIFTON, NEW JERSEY

F-8207 *
F-8207J
POWER
DIODES

DESCRIPTION

Tube types F-8207 and F-8207J are diodes designed for rectifier service or in special applications in shunting or charging circuits. The exceptionally rugged construction, free of internal insulators, spring tensioning devices, and fragile elements, make these diodes adaptable to a wide range of uses. The heavy-wall, water-cooled anode is capable of dissipating up to 8 kilowatts at 3.5 gpm. The F-8207J is provided with an integral water jacket and the inlet and outlet water connections are male fittings for quick-connect coupling without tools.

ELECTRICAL

Filament Voltage				15	volts
Filament Current				36	amperes
Filament Starting Current					
Full rated filament voltage may be safely applied to the cold filament					
<u>Maximum Ratings</u>	<u>Shunt</u>	<u>Charging</u>	<u>Rectifier</u>		
Max. Peak Inverse Voltage	30	30	30		kilovolts
Max. Peak Plate Current	100	7.5 rms	20		amperes
Max. Plate Current	-	-	6		avg. amperes

MECHANICAL


Mounting Position				Vertical, Anode up or down
Type of Cooling				Circulating water
Plate Dissipation	8	6	4	kilovolts
Water Flow	3.5	2.3	1.0	gpm
Water Jacket Pressure Drop ‡				
Water Pressure, max.				80 psig
Outlet Water Temperature, max.				70 °C
Max. Glass and Seal Temperature				180 °C
Net Weight, approx.				2 lbs.

‡ The pressure drop across the jacket is negligible compared to the drop in the associated plumbing.

Additional information for specific applications can be obtained from:

Electron Tube Applications Section
ITT Components Division
P.O. Box 412
Clifton, New Jersey


* Formerly our D-1050 and D-1050J



Color Code

Fil. Term. - Yellow
Fil. C. Term. - Red

This tube type is available on request with 1/2" wide flexible copper leads, 6" long.




OUTLINE
F-8207 POWER DIODE




Color Code

Fil. Term. - Yellow
Fil. C. Term. - Red



This tube type is available on request with 1/2" wide flexible copper leads, 6" long.



NOTE-Snaptite fittings, BPHC-4, are req'd in making water connections.

OUTLINE
F-8207J POWER DIODE