




PIOTRON

DESCRIPTION

The GL-851 is a three-electrode, general purpose oscillator, or Class B modulator. The plate of this tube is capable of dissipating 500 to 750 watts.

TECHNICAL INFORMATION

These data are for reference only. For design information refer to specifications.

GENERAL CHARACTERISTICS

Electrical

Number of electrodes	3
Filament voltage	11 volts
Filament current	15.5 amperes
Average characteristics	
Amplification factor, $I_b = 300$ ma	20.5
Grid-plate transconductance	15000 micromhos
Direct interelectrode capacitances	
Grid plate	47 micromicrofarads
Input	25.5 micromicrofarads
Output	4.5 micromicrofarads
Frequency for maximum ratings	3 megacycles

Mechanical

Type of cooling	convection
Maximum ambient temperature	60 centigrade
Net weight, approx.	3 pounds
Mounting position	vertical, filament base (large) up or horizontal, filament in vertical plane (on edge)
Weight, approx.	9 pounds

GENERAL ELECTRIC



TECHNICAL INFORMATION (CONT'D)

MAXIMUM RATINGS AND TYPICAL OPERATING CONDITIONS

				Typical Operation	Maximum Ratings
CLASS A AUDIO-FREQUENCY AMPLIFIER AND MODULATOR					
D-c plate voltage	1500	2000	2500	2500	volts
Plate dissipation				600	watts
D-c grid voltage	-49	-65	-92		volts
Peak grid swing, approx.	44	60	87		volts
D-c plate current	0.175	0.270	0.240		ampere
Plate resistance	1800	1500	1600		ohms
Load resistance	3700	3100	5000		ohms
Plate power output, 5 per cent second harmonic	46	100	160		watts

CLASS B AUDIO-FREQUENCY POWER AMPLIFIER (TWO TUBES)

D-c plate voltage	2000	2500	3000	3000 volts
Max signal plate current, per tube*				1 ampere
D-c max signal plate input, per tube*				2250 watts
Plate dissipation, per tube*				750 watts
D-c grid voltage	-85	-111	-135	volts
Peak a-f grid input voltage	250	245	245	volts
Zero signal plate current	0.12	0.12	0.11	ampere
Max signal plate current	1.7	1.4	1.2	amperes
Max signal plate input*	3400	3500	3600	watts
Max signal driving power, approx.	20	12	6	watts
Effective load resistance, plate-to-plate	2600	4000	5600	ohms
Max signal plate power output	2200	2300	2400	watts

CLASS B RADIO-FREQUENCY POWER AMPLIFIER

Carrier conditions per tube for use with a max modulation factor of 1.0

D-c plate voltage	1500	2000	2500	2500 volts
D-c grid voltage	-60	-85	-110	volts
D-c plate current	0.62	0.475	0.39	0.750 ampere
Plate input				1100 watts
Plate dissipation				750 watts
Peak r-f grid input voltage	300	280	270	volts
Driving power, approx†	40	25	20	watts
Plate power output	275	300	325	watts

CLASS C RADIO-FREQUENCY POWER AMPLIFIER AND OSCILLATOR—PLATE-MODULATED

Carrier conditions per tube for use with a max modulation factor of 1.0

D-c plate voltage	1500	2000	2000	volts
D-c grid voltage	-250	-300	-500	volts
D-c plate current	0.9	0.85	1	ampere
D-c grid current, approx.	0.15	0.125	0.200	ampere
Plate input			1800	watts
Plate dissipation			500	watts
Peak r-f grid input voltage, approx.	475	525		volts
Driving power, approx.	75	65		volts
Plate power output	900	1250		watts

CLASS C RADIO-FREQUENCY POWER AMPLIFIER AND OSCILLATOR

Key-down conditions per tube without modulation‡

D-c plate voltage	1500	2000	2500	2500 volts
D-c grid voltage	-150	-200	-250	-500 volts
D-c plate current	0.9	0.9	0.9	1 ampere
D-c grid current, approx.	0.15	0.12	0.1	0.200 ampere
Plate input				2500 watts
Plate dissipation				750 watts
Peak r-f grid input voltage, approx.	375	425	450	volts
Driving power, approx.	55	50	45	watts
Plate power output	900	1250	1700	watts

* Averaged over any audio-frequency cycle.

† At crest of audio-frequency cycle.


‡ Modulation, essentially negative, may be used if the positive peak of the audio-frequency envelope does not exceed 115 per cent of the carrier conditions.


APPLICATION NOTES

GL-851 can be operated at maximum ratings in all classes of service at frequencies as high as 3 megacycles. The tube may be operated at higher frequencies provided the maximum values of plate voltage and power input are reduced as the frequency is raised. (Other maximum ratings are the same as shown under TECHNICAL

INFORMATION.) The tabulation below shows the highest percentage of maximum plate voltage and power input that can be used up to 15 mc for the various classes of service. Special attention should be given to adequate ventilation of the bulb at these frequencies.


Frequency	3	7	15 megacycles
Maximum permissible percentage of maximum rated plate voltage and plate input:			
Class B telephony	100	88	76 per cent
Class C telephony, plate-modulated	100	75	50 per cent
Class C telegraphy, plate-modulated	100	75	50 per cent





K-6966441

11-2-44



K-2636625

9-23-44

OUTLINE
GL-851 PIOTRON