




**MINIATURE
OUTPUT PENTODE
0·3A INDIRECTLY HEATED**

N329
MARCH, 1954

A high slope pentode suitable for use as an audio and frame time base output valve.

BASE CONNECTIONS AND VALVE DIMENSIONS



View from underside
of base.

Base : B9A
Bulb : Tubular

Overall length : 78·5 max. mm.
Seated length : 71·5 max. mm.
Diameter : 22·2 max. mm.

HEATER

I_h	0·3	A
V_h	16·5	V

MAXIMUM RATINGS (design centre)

V_a (b)	550	V	V_{h-k}	250	V
V_{g2} (b)	550	V	I_k	75	mA
V_a	250	V	P_a	9	W
* V_a (pk) pulse	2,500	V	P_{g2}	2·5	W
V_{g2}	250	V			

*Maximum pulse duration 10% of one cycle with a maximum of 2 m sec.

CHARACTERISTICS

V_a	170	V	g_m	9·0	mA/V
V_{g2}	170	V	r_a	20,000	k Ω
V_{g1}	-10·4	V	μ (g_1 - g_2)	10	
I_a	53	mA			

CAPACITANCES (of cold valve)

C_{g1-a}	1·0 pF	C_{g1-all}	11 pF	C_{a-all}	6·2 pF
------------	--------	--------------	-------	-------------	--------

TYPICAL OPERATION. Pentode Connection.

Single Valve. Class A. Audio Amplifier.

V_a	170	200	V
V_{g2}	170	200	V
V_{g1} (o)	-10·6 approx.	-14·4 (approx.)	V
v_{in} pk	8·5	9·9	V
i_a (o)	50	45·0	mA
i_{g2} (o)	9	8·5	mA
R_k	180	270	Ω
R_L	3	4	k Ω
P_{out}	4·0	4·2	W
D	10	10	%

MOUNTING Any position.

SCREENING None normally required.


RETAINING The use of a retaining device is recommended.


VENTILATION


Free air circulation around the bulb is preferable. The temperature of the hottest part of the bulb must not exceed 250°C.


MICROPHONY

The valve is free from microphony in normal receiver application.









N329