

R.F. POWER TETRODE

QV04-7

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.

This data sheet should be read in conjunction with "Operating Notes, Part I—Power Valves," included in this volume of the Handbook.

CATHODE

Indirectly heated.

V_h	6.3	V
I_h	0.6	A
Heating time	22	secs.

CAPACITANCES

C_{in}	8.0	$\mu\mu F$
C_{out}	5.4	$\mu\mu F$
C_{a-gl}	< 0.1	$\mu\mu F$

CHARACTERISTICS at $V_a=300$ V; $V_{g2}=250$ V; $I_a=25$ mA.

g_m	1.9	mA/V
μ_{g1-g2}	5.6	
r_u	67	k Ω

LIMITING VALUES

V_a max.	400	V
V_{g2} max.	250	V
p_a max.	7.5	W
p_{g2} max.	2.0	W
I_k max.	50	mA
I_{g1} max.	6.0	mA

QV04-7

R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.

OPERATING CONDITIONS FOR SINGLE VALVE CLASS "C" R.F. AMPLIFIER

	3	3	20	20	Mc/s
f	300	300	300	300	V
V _a	150	250	150	250	V
V _{g2}	-35	-50	-30	-60	V
V _{g1}	40	43	43.5	43.7	mA
I _a	7.2	6.6	4.7	5.9	mA
I _{g2}	2.8	0.4	1.8	0.4	mA
I _{g1}	58	60	48	67	V
V _{in(pk)}	4.9	4.8	5.8	5.2	W
P _a	7.1	8.1	7.3	7.9	W
P _{out}	59	62	56	60	%
η	60	60	150	150	Mc/s
f	300	300	300	300	V
V _a	150	250	150	250	V
V _{g2}	-30	-50	-30	-50	V
V _{g1}	44	44	44	46	mA
I _a	4.5	6.0	4.5	4.0	mA
I _{g2}	1.9	0.4	1.5	0.4	mA
I _{g1}	48	57	52	57	V
V _{in(pk)}	6.2	5.5	6.9	7.5	W
P _a	7.0	7.7	6.3	6.3	W
P _{out}	53	58	48	46	%
η					

OPERATING CONDITIONS FOR TWO VALVES CLASS "C" R.F. AMPLIFIER

	60	100	150	Mc/s
f	300	300	300	V
V _a	250	250	250	V
V _{g2}	-60	-60	-50	V
V _{g1}	2 × 43	2 × 44.4	2 × 46	mA
I _a	2 × 6.7	2 × 5.3	2 × 4.0	mA
I _{g2}	2 × 0.5	2 × 0.4	2 × 0.4	mA
I _{g1}	2 × 68	2 × 68	2 × 57	V
V _{in(pk)}	2 × 5.1	2 × 6.0	2 × 7.4	W
P _a	15.6	14.7	12.6	W
P _{out}	60	55	46	%
η				

OPERATING CONDITIONS FOR SINGLE VALVE FREQUENCY DOUBLER

	20	75	100	150	Mc/s
f _{out}	300	300	300	250	V
V _a	250	250	200	200	V
V _{g2}	-80	-120	-120	-120	V
V _{g1}	41	43.5	38.4	36.8	mA
I _a	8.0	5.5	2.6	2.1	mA
I _{g2}	0.8	1.2	1.5	1.1	mA
I _{g1}	81	124	120	144	V
V _{in(pk)}	6.8	7.4	7.1	6.9	W
P _a	5.6	5.6	4.4	2.3	W
P _{out}	45	44	38	25	%
η					



R.F. POWER TETRODE


QV04-7

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.

OPERATING CONDITIONS AS FREQUENCY TREBLER

	Single Valve			Push-Pull	
f_{out}	20	75	100	150	Mc/s
V_a	300	300	275	225	V
V_{g2}	250	250	200	200	V
V_{g1}	-120	-140	-140	-140	V
I_a	35	34	36	2×36	mA
I_{g2}	4.2	2.8	2.5	2×2.5	mA
I_{g1}	0.6	0.6	1.5	2×1.3	mA
$V_{in(pk)}$	109	130	142	2×152	V
P_a	7.3	7.1	7.1	2×6.6	W
P_{out}	3.3	3.2	2.8	3.1	W
η	31	31	28	19	%

WEIGHT Valve only ; $1\frac{1}{2}$ oz.



237


Parallel-line Push-pull R.F. Amplifier

QV04-7


R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.

DIMENSIONS AND BASE CONNECTIONS



9-PIN PRESSED GLASS BASE TO FIT B9G VALVE HOLDER




[238]

R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.

QV04-7




ANODE CURRENT PLOTTED AGAINST ANODE VOLTAGE. $V_{g2} = 150V$

QV04-7

R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier.




ANODE CURRENT PLOTTED AGAINST ANODE VOLTAGE. $V_{g2} = 250V$

R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s., as an R.F. amplifier or as a frequency multiplier

QV04-7




GRID CURRENT PLOTTED AGAINST ANODE VOLTAGE $V_{g2} = 250V$

QV04-7

R.F. POWER TETRODE

Indirectly heated Beam Tetrode with aligned grid construction to minimise screen current. It is rated to dissipate a maximum of 7.5 watts at the anode, and is particularly suitable for use at frequencies up to 150 Mc/s, as an R.F. amplifier or as a frequency multiplier.



FREQUENCY CHARACTERISTICS