

Central ELECTRONIC

MANUFACTURERS

DENVILLE, NEW JERSEY

HIGH
VACUUM
DIODE

XD - 27

DESCRIPTION

The Central XD-27 is a high vacuum high current diode of the low impedance type. This thoriated tungsten filament tube was designed for rectifier or clipper service, and is available in both water and air cooled versions.

SPECIFICATIONS:

PHYSICAL

	Water	Air
Length	9 7/16	6 1/2 inches
Diameter	4	4 5/8 inches
Weight	1 1/2	5 1/2 Pounds (approx.)
Mounting Position	Vertical	Vertical
Mounting Socket (air version)		CAS-A or CAS-B series
Type of Cooling		

	Air		Water	
Velocity (cfm)	Anode Dissipation (Kw)	Pressure (in. of water)	Flow (gpm)	Anode Dis. (Kw)
50	1.0	0.20	3	5
75	1.8	0.26		
125	2.4	0.58		
190	3.0	1.21		

Max. Incoming Air Temperature
Max. Glass Seal Temperature
Max. Outlet Temperature

45° C (air version)
180° C (air version)
70° C (water version)

ELECTRICAL (RECTIFIER)

Filament	Thoriated Tungsten
Filament Voltage	13.0 Volt
Filament Current	36.0 Ampere
Peak Inverse Voltage (max.)	30 Kilovolts
Average Anode Current	3 Amperes
Peak Anode Current (max.)	15 Amperes

ELECTRICAL (CLIPPER)

Filament Voltage	14.5 Volts
Filament Current	40.0 Amperes
Peak Inverse Voltage (max.)	30 Kilovolts
Peak Anode Current (max.)	150 Amperes
RMS Anode Current	6 Amperes


X-RAY INFORMATION

WARNING FOR POSSIBLE X-RAY GENERATION


See Safety Code for the Industrial Use of X-Rays published by the American Standards Association.

Over

XD-27 AIR



XD-27 WATER



PROVISIONAL DATA

Issued 8-60

Check factory before finalizing designs.



