

OBJECTIVE TECHNICAL INFORMATION

These ratings represent the design objective for this product. Refer to the Preliminary Technical Information sheet for ratings currently achieved in the progression towards design objectives. If PTI sheets do not exist, consult your local Tube Department Regional Sales Office.

DEVELOPMENTAL TYPE

ZP-1043
OTI-90
Page 1
3-15-64

This technical information is proprietary and is furnished only as a service to customers

ZP-1043

TRIODE

Grid-Pulsed Amplifier Service
Grounded-Grid Operation

Heat-Sink and Forced-Air Cooled
Metal and Ceramic

The ZP-1043 is a heat-sink-cooled triode especially designed for grid-pulsed amplifier service in L-band. This tube is particularly well suited for use in navigational aid application. Features include small size, long pulse width and high duty capability, long life and reliability.

ELECTRICAL

Heater Voltage*	5.0	Volts
Heater Current	2.4	Amperes
Cathode Heating Time, minimum	1	Minute
Direct Interelectrode Capacitances		
Input	16.5	μ f
Output	4.0	μ f
Plate-Cathode	0.1	μ f

MECHANICAL

Mounting Position - Any		
Net Weight, approximately	2-1/2	Ounces

THERMAL

Cooling - Heat-sink or Forced air		
Maximum Anode Temperature §	250	C
Maximum Ceramic Temperature at Any Point	200	C

GRID-PULSED AMPLIFIER - CLASS C

Maximum Ratings		
DC Plate Voltage	2.5	Kilovolts
DC Plate Current, during pulse	3.0	Amperes
DC Grid Voltage	-200	Volts
Plate Dissipation	50	Watts
Pulse Width ¶	10	Microseconds
Duty Factor ◇¶	0.01	

Typical Operation

Grounded-Grid Circuit at 1150 mcs, 1/4 λ Output		
DC Plate Voltage	2000	2000 Volts
DC Plate Current, during pulse	1.1	2.25 Amperes
DC Grid Voltage	-80	-80 Volts
DC Grid Current, during pulse	0.35	0.75 Amperes
Power Output, during pulse (useful)	1000	2000 Watts
Drive Power, during pulse	200	350 Watts
Pulse Width ◇	10	10 Microseconds
Duty Factor	0.01	0.004

- * Because of back-heating due to transit time effects, it may be necessary to reduce the heater voltage.
- § A suitable heat-sink clamping arrangement must be provided to limit the anode hub temperature to the value specified.
- ¶ Maximum ratio of on-time to elapsed time during any 250 microsecond period.
- ◇ Pulse duration is measured between points at 70 percent of the peak value. The peak value is defined as the maximum value of a smooth curve through the average of the fluctuations over the top portion of the pulse.
- ¶ For recommendations on longer pulse width and higher duty factor refer to the manufacturer.

The specifications of this type are subject to change. This device is now under development and is made available for experimental purposes only. For the most recent information concerning the status of this development, please consult your local Tube Department Regional Sales Office, or current Preliminary Technical Information for the same catalog number.

