



ELECTRONIC TUBE REFERENCE

11FP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Eleven-inch P4 cathode-ray picture tube for direct-view display service. RMA/EIA documentation gives typical anode operation near 10 kV; the available source supports a conventional high-voltage picture-tube classification without additional specialized claims.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 450 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray

No fixed ratings recorded.

CRT anode/ultor voltage is represented in MaxPlateVoltage; additional electrode, drive, optical, and capacitance data retained as parameters.

The 11FP4 is a direct-view cathode-ray television picture tube. The supplied sheet specifies its focus/deflection system, high-voltage anode operation, heater requirements, electrode ratings, and picture-tube mechanical/optical characteristics.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1964 RMA EIA

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1964 RMA EIA

Section 1 · Cathode Ray

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical anode voltage	10000 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker