



ELECTRONIC TUBE REFERENCE

12AMP25

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Twelve-inch electrostatically focused and deflected cathode-ray display tube with an aluminized P25 screen. Its orange fluorescence has very long persistence, making trace retention a defining feature for direct-view instrument displays.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray*No fixed ratings recorded.**Cathode-ray display/electron-gun section.*



SOURCE OPERATING CONDITIONS

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic text	—
Phosphor	P25 text	—
Fluorescence	Orange text	—
Persistence	Very long text	—
Screen Construction	Aluminized/metal-backed text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker