



ELECTRONIC TUBE REFERENCE

12BQ6GTA

Power - TV Horizontal Output (sweep) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
BEAMPOWER

Improved television horizontal-output beam-power tube rated for approximately 6 kV positive plate pulses and substantial current in CRT line-deflection service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	6AM	BASE PINS	7
NOMINAL HEATER	12.6 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

6AM - TERMINAL PINOUT

TERMINAL	SECTION	ELEMENT	STATUS
PIN1 – Pin 1	–	–	NC · verified
PIN2 – Pin 2	–	H – Heater	CONNECTED · verified
PIN3 – Pin 3	–	–	NC · verified
PIN4 – Pin 4	A	G2 – Screen Grid	CONNECTED · verified
PIN5 – Pin 5	A	G1 – Control Grid	CONNECTED · verified
PIN7 – Pin 7	–	H – Heater	CONNECTED · verified
PIN8 – Pin 8	A	BP – Beam-Forming Plate	CONNECTED · verified
PIN8 – Pin 8	A	K – Cathode	CONNECTED · verified

TERMINAL	SECTION	ELEMENT	STATUS
CAP1 – Top cap	A	P – Plate (Anode)	CONNECTED · verified

SECTION RATINGS

SECTION1 Beam Power	
PLATE RESISTANCE	20000 Ω
TRANSCONDUCTANCE	0.0055 S
MAXIMUM PLATE VOLTAGE	600 V
MAXIMUM SCREEN VOLTAGE	175 V
MAXIMUM PLATE DISSIPATION	11 W
MAXIMUM SCREEN DISSIPATION	2.5 W
MAXIMUM CATHODE CURRENT	110 mA
<i>Published ratings/characteristics promoted where semantically applicable.</i>	

Improved beam-power horizontal-deflection output pentode for television line-output service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Beam Power

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Input capacitance	15 pF	—
Output capacitance	7 pF	—
Grid-to-plate capacitance	0.55 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate voltage	250 V	HorizontalDeflection
Screen voltage	150 V	HorizontalDeflection
Grid voltage	-22.5 V	HorizontalDeflection
Plate current	55 mA	HorizontalDeflection
Positive pulse plate voltage	6000 V	HorizontalDeflection

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Westinghouse Data Book

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 WESTINGHOUSE DATA BOOK

Section 1 · Beam Power

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
DC plate supply voltage maximum	600 V	—
Peak positive plate voltage maximum	6000 V	Pulse
Peak negative plate voltage maximum	-1250 V	Pulse
Plate dissipation maximum	11 W	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Television horizontal-deflection output amplifier	—