



ELECTRONIC TUBE REFERENCE

12HP1

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

12HP1 12-inch P1 phosphor cathode-ray tube with electrostatic focusing and two-axis electrostatic deflection, 6.3 V 0.6 A heater.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	11
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray**MAXIMUM PLATE VOLTAGE** 5500 V

12HP1 electrostatic focus/deflection CRT. Maximum anode2 high voltage 5500 V; anode1 focusing electrode max 1500 V; control grid never positive. Peak anode2-to-deflection-plate voltage ≤ 1000 V. Grid circuit resistance max 1.5 M Ω , deflection supply impedance at heater frequency max 1 M Ω . Typical anode2 5000 V, focus anode1 1150 V (+25%/-30%), grid cutoff -90 $\pm$ 50 V. Deflection factors D1-D2 19 V/(inch kV) $\pm$ 20%, D3-D4 25 V/(inch kV) $\pm$ 20%. P1 phosphor. Capacitances control grid-to-other ≤ 12 pF, deflection pair ≤ 3 pF, deflection plate to others ≤ 11 pF. 11-pin Magal, RMA basing 11J.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker