



ELECTRONIC TUBE REFERENCE

14A4

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Medium-mu receiving triode with a 12.6 V, 150 mA heater, intended for general small-signal amplification in series-heater electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	5AC	BASE PINS	5
NOMINAL HEATER	12.6 V / 150 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	7700 Ω
TRANSCONDUCTANCE	0.0026 S
AMPLIFICATION FACTOR	20
MAXIMUM PLATE VOLTAGE	300 V
<i>Published maximum ratings, operating characteristics, and continuation data reviewed.</i>	

14A4 is listed in the supplied receiving-tube handbook as a medium-mu triode. The published heater rating is 12.6 V at 0.15 A.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

195X General Electric Essential Characteristics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

195X GENERAL ELECTRIC ESSENTIAL CHARACTERISTICS

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum plate voltage	300 V	Published handbook rating
Plate voltage	250 V	ClassA
Control-grid bias	8 V	ClassA
Plate current	9 mA	ClassA

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate resistance	7700 ohm	Published handbook characteristic
Transconductance	2600 μ S	Published handbook characteristic
Amplification factor	20	Published handbook characteristic
Heater voltage	12.6 V	Published heater rating
Heater current	150 mA	Published heater rating

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker