



ELECTRONIC TUBE REFERENCE

15EAY

Power - TV Vertical Output electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TRIODE

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	13 V / 450 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Dissimilar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	40000 Ω
TRANSCONDUCTANCE	0.0016 S
AMPLIFICATION FACTOR	64
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	1.5 W

SECTION2 Triode	
PLATE RESISTANCE	750 Ω
TRANSCONDUCTANCE	0.0072 S
AMPLIFICATION FACTOR	5.4
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	10 W

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 RCA RC26

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 RCA RC26

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	250 V	—
Grid Bias	-3 V	—
Plate Current	1.4 mA	—
Grid To Plate Capacitance	4.8 pF	—

1968 RCA RC26

Section 2 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Plate Voltage	150 V	—
Grid Bias	-20 V	—
Plate Current	50 mA	—
Grid To Plate Capacitance	10 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker