

ELECTRONIC TUBE REFERENCE

19FJP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
CATHODERAY

Wide-angle aluminized P4 monochrome television picture tube using electrostatic focusing and magnetic deflection, designed for high-voltage direct-view service with a large approximately 19-inch screen.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 450 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray
No fixed ratings recorded.
Television CRT electron-gun/display section.

The 19FJP4 is a 19-inch television picture tube; supplied JEDEC registration states it is identical to 19EHP4 except for 0.45 A heater current.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1964 RMA EIA

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1964 RMA EIA

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	450 mA	—
Heater Warm-up Time	11 s	—
Focusing Method	Electrostatic text	—
Deflection Method	Magnetic text	—
Horizontal Deflection Angle	102 deg	—
Vertical Deflection Angle	85 deg	—
Diagonal Deflection Angle	114 deg	—
Cathode-to-All Capacitance	5 pF	Approximate
Grid1-to-All Capacitance	6 pF	Approximate
External Coating-to-Anode Capacitance Minimum	1000 pF	—
External Coating-to-Anode Capacitance Maximum	1500 pF	—
Phosphor	P4 Aluminized text	—
Fluorescence	White text	—
Light Transmittance	49 percent	ScreenCenter
Electrical Characteristics Reference	19EHP4 text	IdenticalExceptHeaterCurrent

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker