

ELECTRONIC TUBE REFERENCE

19WP12

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Cathode-ray display tube using a P12 orange medium-long-persistence screen, with electrostatic focusing and combined electrostatic/magnetic deflection in the Du Mont display-tube family.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray
<i>No fixed ratings recorded.</i>
<i>Cathode-ray display/electron-gun section.</i>



SOURCE OPERATING CONDITIONS

1960 Du Mont

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 DU MONT

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Electrostatic and Magnetic text	—
Phosphor	P12 text	—
Fluorescence	Orange text	—
Persistence	Medium-long text	—
Deflection Angle	66 deg	Approximate
Screen Construction	Aluminized/metal-backed text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker