



ELECTRONIC TUBE REFERENCE

1K20XK

Specialized - Klystron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
KLYSTRON

Ceramic-metal reflex klystron designed for microwave oscillator service in its specified C- or X-band frequency range.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 800 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Klystron

MAXIMUM CATHODE CURRENT	55 mA
-------------------------	-------

Reflex klystron: specialized resonator/repeller ratings have no direct promoted columns and are preserved in TUBE_SECTION_PARAMETER; published maximum cathode current is promoted.

X-band reflex klystron for oscillator service with the frequency and output characteristics published on its Eimac datasheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1962 Eimac

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1962 EIMAC

Section 1 · Klystron

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Frequency Range	9200–10000 MHz	—
Published Output Power	75 mW	Minimum or typical as stated by source
Warm-up Time	30 s	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum DC Resonator Voltage	350 V	—
Maximum Resonator Dissipation	20 W	—
Maximum Negative Repeller Voltage	500 V	Negative with respect to cathode
Maximum Positive Repeller Voltage	0 V	Positive with respect to cathode
Typical DC Resonator Voltage	350 V	—
Typical DC Cathode Current	50 mA	—
Typical Power Output	90 mW	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker