

Twenty-inch direct-view monochrome television picture tube with magnetic deflection and a white P4 screen. Manufacturer data specifies high-voltage CRT operation and focusing characteristics for large-screen receiver display service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	12L	BASE PINS	6
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	16000 V
MAXIMUM SCREEN VOLTAGE	500 V
CRT section; LowVoltageElectrostatic focus with magnetic deflection.	

Direct-view television picture tube with lowvoltageelectrostatic focus, magnetic deflection, P4 white phosphor, and published high-voltage CRT operating data.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	Nominal
Heater current	600 mA	Nominal
Anode voltage	14 V	Published CRT data
Grid 2 voltage	16 V	Published CRT data

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Deflection angle	66 deg	Published CRT data



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1966 Tung Sol Electronic Tubes 4 of 4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1966 TUNG SOL ELECTRONIC TUBES 4 OF 4

Section 1 · Cathode Ray

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	LowVoltageElectrostatic	—
Deflecting method	Magnetic	—
Phosphor	P4	White

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Horizontal deflection angle	66 deg	Approximate
Diagonal deflection angle	70 deg	Approximate
Persistence	Short	—
Faceplate light transmission at center	68.25 %	Approximate

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode to all other electrodes capacitance	5 pF	Approximate
Grid #1 to all other electrodes capacitance	6 pF	Approximate

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	—
Heater current	600 mA	—
Maximum DC anode voltage	16000 V	—
Maximum DC grid #2 voltage	500 V	—
Maximum grid #1 negative bias magnitude	125 V	—
Maximum grid #1 positive DC bias	0 V	—
Maximum grid #1 positive peak	2 V	—
Maximum heater-cathode voltage during warm-up	410 V	HeaterNegative;Warmup<=15s
Maximum heater-cathode voltage after warm-up	150 V	HeaterNegative
Maximum heater-cathode voltage heater positive	150 V	HeaterPositive
Typical DC anode voltage	14000 V	TelevisionPictureTube
Typical DC grid #2 voltage	300 V	TelevisionPictureTube
Typical grid #1 visual-extinction range	-33 to -77 V	VisualExtinction
Ion trap setting	35 gauss	Approximate

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum focusing-electrode voltage range	-1000 to +2000 V	—
Typical focusing-electrode voltage	0 V	—



SOURCE OPERATING CONDITIONS

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO
Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical Anode Voltage	14000 V	—
Typical Grid No. 2 Voltage	300 V	—
Grid No. 1 Maximum Negative Bias	125 V	—
Grid No. 1 Maximum Positive Peak	2 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker