



ELECTRONIC TUBE REFERENCE

20P2

Power - TV Horizontal Output (sweep) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

BEAMPOWER

Television beam-power amplifier for series-heater operation, rated for high pulse anode voltage and intended for demanding television output service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	38 V / 200 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Beam Power	
TRANSCONDUCTANCE	0.0135 S
MAXIMUM PLATE VOLTAGE	400 V
MAXIMUM SCREEN VOLTAGE	250 V
MAXIMUM PLATE DISSIPATION	20 W
MAXIMUM SCREEN DISSIPATION	5 W

Television beam power amplifier for series operation.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Beam Power

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum peak anode voltage	5000 V	Pulse