



ELECTRONIC TUBE REFERENCE

210LF

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Cossor directly heated triode for low-frequency receiver amplification, using a low-power two-volt filament.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	2 V / 100 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	10000 Ω
TRANSCONDUCTANCE	0.0014 S
AMPLIFICATION FACTOR	14
MAXIMUM PLATE VOLTAGE	150 V
<i>Published ratings and characteristics promoted from approved datasheet.</i>	

Cossor 210LF triode for receiver/amplifier service as specified in the supplied catalogue datasheet.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker