



ELECTRONIC TUBE REFERENCE

215SG

Voltage - Tetrode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TETRODE

Screen-grid tetrode intended for receiver voltage amplification, detector, oscillator, or general Class-A service as documented by the manufacturer.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	2 V / 150 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Tetrode	
PLATE RESISTANCE	300000 Ω
TRANSCONDUCTANCE	0.0011 S
MAXIMUM PLATE VOLTAGE	150 V
<i>Published ratings and characteristics promoted from approved datasheet.</i>	

Cossor 215SG tetrode for receiver/amplifier service as specified in the supplied catalogue datasheet.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker