



ELECTRONIC TUBE REFERENCE

21AUP4A

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Large P4 monochrome television picture tube documented for high-voltage direct-view service, using magnetic deflection and manufacturer-specified focusing and beam-control arrangements for type 21AUP4A.

GENERAL CHARACTERISTICS

BASE DESIGNATION	12L	BASE PINS	6
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	20000 V
MAXIMUM SCREEN VOLTAGE	500 V
CRT ratings, operating conditions, capacitances, optical and deflection data retained as parameters.	

Direct-view cathode-ray picture tube for television display service. Electrical ratings, operating conditions, capacitances, optical data, and construction details were extracted from the supplied datasheet.



SOURCE OPERATING CONDITIONS

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	Nominal
Heater current	600 mA	Nominal
Maximum grid 2 voltage	500 V	—
Typical grid 2 voltage	500 V	Typical operating conditions

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Horizontal deflection angle	67 deg	—
Vertical deflection angle	53 deg	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode to all other electrodes	1 pF	Approximate



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1966 Tung Sol Electronic Tubes 4 of 4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1966 TUNG SOL ELECTRONIC TUBES 4 OF 4

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HEATER	6.3 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
HEATER POSITIVE WITH RESPECT TO CATHODE	18 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #4 VOLTAGES – value 1	4 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #4 VOLTAGES – value 2	72 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #4 VOLTAGES – value 3	396 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #2 VOLTAGE – value 1	2 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #2 VOLTAGE – value 2	3 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC ION TRAP MAGNET (RATED STRENGTH)D	46 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
VOLTAGE SHOULD NO BE 1E55 TX AN 14,000 VOLTS. – value 1	1 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
VOLTAGE SHOULD NO BE 1E55 TX AN 14,000 VOLTS. – value 2	14 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
VOLTAGE SHOULD NO BE 1E55 TX AN 14,000 VOLTS. – value 3	0 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
BFOR FOCUS WITH ANODE CURRENT OF 100 uAMP S.	100	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
I NAGMULH AS THE TUBE RATING PERMITS OPERATION AT VOLTAGES AS HIGH AS 19.8 KILOVOLTS LAB GOLU TE	19.8 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
LONDI TIONS INVOLVE	16 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MAXIMUM DC ANODE, GRID #3, GRID #5 VOLTAGE A – value 1	5 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC ANODE, GRID #3, GRID #5 VOLTAGE A – value 2	2 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC ANODE, GRID #3, GRID #5 VOLTAGE A – value 3	18 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #2 VOLTAGE – value 1	2 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #2 VOLTAGE – value 2	5 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 CIRCUIT RESISTANCE – value 1	1 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 CIRCUIT RESISTANCE – value 2	1 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 CIRCUIT RESISTANCE – value 3	5 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.



SOURCE OPERATING CONDITIONS

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical Anode Voltage	16000 V	—
Typical Grid No. 2 Voltage	300 V	—
Grid No. 1 Maximum Negative Bias	125 V	—
Grid No. 1 Maximum Positive Peak	2 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#)[Tube types](#)[Full books](#)[Blog](#)[Feedback & corrections](#)

© 2026 Tube Tinker