

ELECTRONIC TUBE REFERENCE

21CGP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Large P4 monochrome television picture tube documented for high-voltage direct-view service, using magnetic deflection and manufacturer-specified focusing and beam-control arrangements for type 21CGP4.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	12
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	20000 V
MAXIMUM SCREEN VOLTAGE	200 V
Published promoted fields populated by printed ratings/characteristics headings.	

Direct-view cathode-ray picture tube for television display service. Electrical ratings, operating conditions, capacitances, optical data, and construction details were extracted from the supplied datasheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HighVoltageAnodeMaximum	20000 V	CRT

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
CathodeToOtherElectrodesCapacitance	5 pF	Approximate



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1966 Tung Sol Electronic Tubes 4 of 4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1966 TUNG SOL ELECTRONIC TUBES 4 OF 4

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
GRID #1 TO ALL OTHER ELECTRODES – value 1	1	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
GRID #1 TO ALL OTHER ELECTRODES – value 2	1	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MINIMUM EXTERNAL CO NO UCTIVE COATING TO ANODE	2000	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HEATER	18 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
Dc ANODE voLTAGE*	1 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID – value 1	4 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID – value 2	3 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #2 VOLTAGE – value 1	2 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #2 VOLTAGE – value 2	11 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
DC GRID #i VOLTAGE B	32 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
THIS TUBE MAY BE OPERATED IN GRID DRIVE IF DESIRED, WITH SOME LOSS IN EFFICIENCY. AVERAGE RASTER	6 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
CUTOFF, WITH GRID OFF, MAY BE CALCULATED: $E_{g1} = 0.502 E_{g2} + 5.8$	5.8 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MAXIMUM EXTERNAL CONDUCTIVE COATING TO ANODE	2500 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC ANODE	20 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #4 VOLTAGE – value 1	4 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #4 VOLTAGE – value 2	500 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MAXIMUM DC GRID #4 VOLTAGE – value 3	1000 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #2 VOLTAGE – value 1	2 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM DC GRID #2 VOLTAGE – value 2	200 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 VOLTAGE	1 V	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 CIRCUIT RESISTANCE – value 1	1 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.
MAXIMUM GRID #1 CIRCUIT RESISTANCE – value 2	1.5 mA	Published CRT datasheet value; multiple values on a row correspond to separate source-table conditions or limits.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker