

ELECTRONIC TUBE REFERENCE

21DWP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Twenty-one-inch direct-view monochrome television picture tube with magnetic deflection and a P4 display screen. Manufacturer documentation places it in the high-voltage receiver CRT family, with construction optimized for bright rectangular picture presentation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	18000 V
<i>Published electrical limits promoted from the source. Passive microwave reference cavities have their electrical frequency/Q values in TUBE_SECTION_PARAMETER because no applicable promoted frequency field exists in the fixed section schema.</i>	

Twenty-one-inch 110-degree magnetic-deflection rectangular glass picture tube with low-power heater.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1947 Westinghouse

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1947 WESTINGHOUSE

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HeaterVoltageNominal	6.3 V	Nominal
HeaterCurrentNominal	300 mA	Nominal
MaximumElectrodeOrAnodeVoltage	18000 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker