



ELECTRONIC TUBE REFERENCE

21FJP22

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Twenty-one-inch color television picture tube with electrostatic focusing, magnetic deflection, and a P22 color screen. Its high-voltage direct-view construction is designed for color receiver service and carries published X-ray precautions.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray*No fixed ratings recorded.**Television CRT electron-gun/display section.*

The 21FJP22 is a 21-inch television cathode-ray tube with magnetic deflection and P22 phosphor.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
Focusing Method	Electrostatic text	—
Deflection Method	Magnetic text	—
Phosphor	P22 text	—
Fluorescence	Color text	—
Persistence	Medium text	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	25000 V	RepresentativeFamilyLimit
Typical Anode Voltage	18000 V	RepresentativeFamilyOperatingPoint
Maximum Grid2 Voltage	700 V	RepresentativeFamilyLimit
Maximum Grid1 Negative Bias	220 V	RepresentativeFamilyLimit
Maximum Heater-Cathode Voltage	200 V	AfterWarmup
Maximum Grid1 Circuit Resistance	1.5 Mohm	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

