

ELECTRONIC TUBE REFERENCE

21FMP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Twenty-one-inch direct-view monochrome television picture tube with magnetic deflection and high-voltage operation. Manufacturer documentation describes its focusing system, picture-screen construction, and receiver-display characteristics for large-screen television service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
Maximum anode voltage mapped to MaxPlateVoltage; CRT grid/focusing limits retained as parameters rather than mis-promoted as ordinary screen-grid data.	

The 21FMP4 is a 21-inch electrostatic-focus, magnetic-deflection glass picture tube with a non-ion-trap gun designed for low Grid No. 2 voltage cathode-drive operation, an aluminized screen, and external conductive coating.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	22000 V	—
Maximum Grid No. 2 Voltage	100 V	—
Anode Voltage	18000 V	Typical
Heater Voltage	6.3 V	—
Heater Current	600 mA	—