

ELECTRONIC TUBE REFERENCE

21FP4A

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Twenty-one-inch direct-view monochrome television picture tube with magnetic deflection and high-voltage operation. Manufacturer documentation describes its focusing system, picture-screen construction, and receiver-display characteristics for large-screen television service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	12
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	18000 V
MAXIMUM SCREEN VOLTAGE	500 V
Maximum anode voltage mapped to MaxPlateVoltage; CRT grid/focusing limits retained as parameters rather than mis-promoted as ordinary screen-grid data.	

21FP4-family rectangular picture tube with electrostatic focus, magnetic deflection, grey-filter faceplate, and external conductive coating.

SOURCE OPERATING CONDITIONS

1961 Tung Sol

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1961 TUNG SOL

Section 1 · Cathode Ray

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HighVoltageAnodeMaximum	20000 V	CRT

CAPACITANCE

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
CathodeToOtherElectrodesCapacitance	5 pF	Approximate

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1966 Tung Sol Electronic Tubes 4 of 4

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1966 TUNG SOL ELECTRONIC TUBES 4 OF 4

Section 1 · Cathode Ray

CONSTRUCTION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Electrostatic	—
Deflecting method	Magnetic	—
Phosphor	P4	White;MediumPersistence
External conductive coating	Present	—

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Deflection angle	70 deg	Approximate

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Faceplate light transmission at center	66 %	Approximate

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	—
Heater current	600 mA	—
Maximum DC anode voltage	18000 V	—
Maximum DC grid #2 voltage	500 V	—
Maximum grid #1 negative-bias magnitude	125 V	—
Maximum grid #1 positive DC voltage	0 V	—
Maximum grid #1 positive peak voltage	2 V	—
Typical DC anode voltage	14000 V	TelevisionPictureTube
Typical DC grid #2 voltage	300 V	TelevisionPictureTube
Typical grid #1 voltage minimum	-77 V	VisualExtinctionRange
Typical grid #1 voltage maximum	-33 V	VisualExtinctionRange
Maximum grid #1 circuit resistance	1.5 megohm	—
Ion trap magnet rated strength	35 gauss	Approximate
Focusing electrode voltage minimum	-570 V	ElectrostaticFocus
Focusing electrode voltage maximum	330 V	ElectrostaticFocus
Maximum focusing electrode voltage minimum	-500 V	ElectrostaticFocus
Maximum focusing electrode voltage maximum	1000 V	ElectrostaticFocus
X-ray shielding warning	Present	HighAnodeVoltage

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode-to-all-other-electrodes capacitance	5 pF	Approximate

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid #1-to-all-other-electrodes capacitance	6 pF	Approximate

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Direct-view television picture tube	—



SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	18000 V	—
Maximum Grid No. 2 Voltage	500 V	—
Anode Voltage	16000 V	Typical
Heater Voltage	6.3 V	—
Heater Current	600 mA	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#)
[Tube types](#)
[Full books](#)
[Blog](#)
[Feedback & corrections](#)

© 2026 Tube Tinker