



ELECTRONIC TUBE REFERENCE

21ZP4C

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Large P4 monochrome television picture tube for high-voltage direct-view service, using magnetic deflection and manufacturer-specified focusing and beam-control arrangements for type 21ZP4C.

GENERAL CHARACTERISTICS

BASE DESIGNATION	12N	BASE PINS	5
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	20000 V
CRT maximum accelerating/anode/ultor voltage is promoted to MaxPlateVoltage; additional electrode ratings, capacitances, operating conditions, focus/deflection and optical data are preserved as parameters.	

21ZP4C is a picture tube using magnetic focusing and magnetic deflection. The source specifies a P4 screen and publishes CRT accelerating/anode ratings, control and focusing-electrode limits, heater-cathode limits, capacitances, and operating or deflection characteristics.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1971 RCA HB3 Binder 1 of 7

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 RCA HB3 BINDER 1 OF 7

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater current	60 mA	At6.3V
Faceplate light transmission	75 %	Approximate

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode to all other electrodes	5 pF	—
External conductive coating to anode capacitance	—750 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum grid 2 voltage	550 V	—
Maximum grid 1 negative-bias voltage	155 V	NegativeBias
Maximum grid 1 positive-bias voltage	0 V	PositiveBias
Maximum grid 1 positive-peak voltage	2 V	PositivePeak
Maximum grid 1 negative-peak voltage	220 V	NegativePeak
Peak heater-cathode voltage	200 V	HeaterNegativeOperating
Projected screen area	248 in^2	—
Typical anode/ultor voltage	16000 V	—