



ELECTRONIC TUBE REFERENCE

230XP

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Two-volt super-power directly heated output triode for high-quality audio amplification in battery-operated receiving equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.003 S
AMPLIFICATION FACTOR	4
MAXIMUM PLATE VOLTAGE	150 V
<i>Published ratings/characteristics promoted from the approved datasheet.</i>	

Two-volt super-power output triode for high-quality audio amplification.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1936 Cossor Valve Manual

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1936 COSSOR VALVE MANUAL

Section 1 · Triode

OTHER

PARAMETER

PUBLISHED VALUE

CONDITION / NOTE

Optimum load

3500 ohm

Published datasheet value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker