



ELECTRONIC TUBE REFERENCE

23BXP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Twenty-three-inch television picture tube with electrostatic focusing and magnetic deflection. National Video documentation identifies a high-voltage direct-view CRT with an anode rating around 22 kV.

GENERAL CHARACTERISTICS

BASE DESIGNATION	12L	BASE PINS	12
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
MAXIMUM SCREEN VOLTAGE	550 V
MAXIMUM HEATER-CATHODE VOLTAGE	180 V
<i>CRT anode and grid-2 maximum ratings are promoted from the printed ratings block; other CRT-specific focus/drive/deflection values are preserved in parameters.</i>	

23-inch electrostatic-focus, magnetic-deflection picture tube.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1956 National Video

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1956 NATIONAL VIDEO

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical Anode Voltage	18000 V	—
Phosphor	P4	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage Nominal	6.3 V	—
Heater Current Nominal	600 mA	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker