

23CZP4

Specialized - Cathode Ray electronic tube

Twenty-three-inch direct-view monochrome television picture tube with electrostatic focusing, magnetic deflection, and high-voltage operation. Manufacturer data documents its large-screen receiver-display construction, optical characteristics, and picture-tube operating limits.

GENERAL CHARACTERISTICS

BASE DESIGNATION	12L	BASE PINS	–
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	25000 V
MAXIMUM SCREEN VOLTAGE	550 V
High-voltage CRT ratings promoted from source. Sylvania source includes X-ray radiation precautions/warning.	

23-inch direct-view monochrome television CRT with electrostatic focus, magnetic deflection, aluminized P4 screen, and gray/filter faceplate construction.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	600 mA	—
OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	25000 V	—
Grid2 Voltage	550 V	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Electrostatic	—
Deflection method	Magnetic	—
Horizontal deflection angle	80 deg	—
Diagonal deflection angle	92 deg	—
Vertical deflection angle	67 deg	—
Fluorescence	White	—
Persistence	Short to medium	—
Heater voltage	6.3 V	—
Heater current	600 mA	—
CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	Aluminized P4	—
OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	25000 V	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical anode voltage	20000 V	—
Typical focus-electrode voltage maximum	400 V	—
Typical grid2 voltage	300 V	—
Cutoff voltage range	-40 to -76 V	—
Grid1 circuit resistance maximum	1.5 Mohm	—
Anode voltage minimum	12000 V	—
Focus-electrode voltage range	-400 to +1250 V	—
Grid2 voltage maximum	700 V	—
X-radiation precaution	Operate within published maximum anode-voltage rating; source carries X-radiation warning at elevated EHT.	

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid1-to-all capacitance	6 pF	—
External conductive coating to anode capacitance maximum	2500 pF	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Monochrome television picture display	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker