



ELECTRONIC TUBE REFERENCE

23DYP4

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Twenty-three-inch lightweight glass television picture tube with electrostatic focus, magnetic deflection, integral implosion protection, short overall length, non-ion-trap gun, aluminized screen, and external conductive coating.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
Maximum anode voltage mapped to MaxPlateVoltage; CRT grid/focusing limits retained as parameters rather than mis-promoted as ordinary screen-grid data.	

The 23DYP4 is a 23-inch electrostatic-focus, magnetic-deflection lightweight glass picture tube with integral implosion protection, short overall length, non-ion-trap gun, aluminized screen, and external conductive coating.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 General Electric Co

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 GENERAL ELECTRIC CO

Section 1 · Cathode Ray

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	22000 V	—
Maximum Grid No. 2 Voltage	550 V	—
Anode Voltage	18000 V	Typical
Heater Voltage	6.3 V	—
Heater Current	600 mA	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker