

23EWP4A

Specialized - Cathode Ray electronic tube

Large aluminized P4 monochrome television picture tube for high-voltage direct-view service, using electrostatic focusing and magnetic deflection with manufacturer-specified operating characteristics for type 23EWP4A.

GENERAL CHARACTERISTICS

BASE DESIGNATION	8HR	BASE PINS	–
NOMINAL HEATER	6.3 V / 450 mA	PARALLEL HEATER	– / –
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
MAXIMUM SCREEN VOLTAGE	550 V
High-voltage CRT ratings promoted from source. Sylvania source includes X-ray radiation precautions/warning.	

23-inch direct-view monochrome television CRT with electrostatic focus, magnetic deflection, aluminized P4 screen, and gray/filter faceplate construction.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	450 mA	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Anode Voltage	22000 V	—
Grid2 Voltage	550 V	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Electrostatic	—
Deflection method	Magnetic	—
Horizontal deflection angle	100 deg	—
Diagonal deflection angle	114 deg	—
Vertical deflection angle	83 deg	—
Fluorescence	White	—
Persistence	Short to medium	—
Heater voltage	6.3 V	—
Heater current	450 mA	—

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	Aluminized P4	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	22000 V	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical anode voltage	18000 V	—
Typical focus-electrode voltage range	-200 to +200 V	—
Typical grid2 voltage	400 V	—
Cutoff voltage range	-48 to -96 V	—
Grid1 circuit resistance maximum	1.5 Mohm	—
Grid2 voltage minimum	200 V	—
X-radiation precaution	Operate within published maximum anode-voltage rating; source carries X-radiation warning at elevated EHT. —	

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid1-to-all capacitance	6 pF	—
External conductive coating to anode capacitance maximum	2500 pF	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Monochrome television picture display	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#)
[Tube types](#)
[Full books](#)
[Blog](#)
[Feedback & corrections](#)

© 2026 Tube Tinker