



ELECTRONIC TUBE REFERENCE

23GLP4C

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

Large P4 monochrome television picture tube documented by Mazda-Belvu for direct-view service, using high-voltage CRT construction and a white picture-display phosphor.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	20000 V
<i>Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed where applicable.</i>	

59 cm 110-degree self-protected monochrome television picture tube with clear aluminized screen.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1968 Mazda Belvu

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 MAZDA BELVU

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	6.3 V	Published nominal value
Heater or filament current	600 mA	Published nominal value
Screen diagonal	59 cm	Published
Deflection angle	110 deg	Published

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker