



ELECTRONIC TUBE REFERENCE

25L6GT_Y

Power - Beam (NOT sweep) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

BEAMPOWER

Output beam tetrode designed for AC/DC audio equipment, providing power amplification in series-heater receiving and amplifier circuits.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	25 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Beam Power	
PLATE RESISTANCE	30000 Ω
TRANSCONDUCTANCE	0.0095 S
MAXIMUM PLATE VOLTAGE	200 V
MAXIMUM SCREEN VOLTAGE	110 V
<i>Published Brimar ratings and characteristics promoted where applicable; additional data retained as parameters.</i>	

Output beam tetrode for AC/DC audio equipment.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Brimar Radio Valve No 7

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 BRIMAR RADIO VALVE NO 7

Section 1 · Beam Power

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Power output maximum published	4.3 W	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker